

## 1. IDENTIFICATION

**Product identifier**

**Product Name** John Deere Yellow Acrylic Enamel

**Other means of identification**

**Product Code** 17674  
**UN/ID no.** UN1263  
**SKU(s)** 17671, 17674, VLX20011-06-940

**Recommended use of the chemical and restrictions on use**

**Recommended Use** No information available.  
**Uses advised against** No information available

**Details of the supplier of the safety data sheet**

**Manufacturer Address**  
 Van Sickle Paint Mfg. Co.  
 PO Box 82222  
 Lincoln, NE 68501  
 Phone: 402-476-6558  
 Fax: 402-476-6749

**Emergency telephone number**

**Emergency Telephone** Chemtrec 1-800-424-9300

## 2. HAZARDS IDENTIFICATION

**Classification**

**OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

|  |             |
|--|-------------|
| Skin corrosion/irritation                          | Category 2  |
| Germ cell mutagenicity                             | Category 1B |
| Carcinogenicity                                    | Category 1B |
| Reproductive toxicity                              | Category 2  |
| Specific target organ toxicity (repeated exposure) | Category 2  |
| Aspiration toxicity                                | Category 1  |
| Flammable liquids                                  | Category 2  |

**Emergency Overview**

**Danger**

**Hazard statements**

Causes skin irritation  
 May cause genetic defects  
 May cause cancer  
 Suspected of damaging fertility or the unborn child  
 May cause damage to organs through prolonged or repeated exposure  
 May be fatal if swallowed and enters airways  
 Highly flammable liquid and vapor

**Appearance** No information available**Physical state** liquid**Odor** No information available**Precautionary Statements - Prevention**

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Wash face, hands and any exposed skin thoroughly after handling  
 Do not breathe dust/fume/gas/mist/vapors/spray  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Use explosion-proof electrical/ ventilating/ lighting/ equipment

**Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention  
 If skin irritation occurs: Get medical advice/attention  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 Wash contaminated clothing before reuse  
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
 Do NOT induce vomiting  
 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Precautionary Statements - Storage**

Store locked up  
 Store in a well-ventilated place. Keep cool

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other Information**

Unknown acute toxicity 0.39% of the mixture consists of ingredient(s) of unknown toxicity

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name                    | CAS No.    | Weight-% | Trade Secret |
|----------------------------------|------------|----------|--------------|
| Solvent Naphtha, Light Aliphatic | 64742-89-8 | 10 - 30  | *            |
| Xylene                           | 1330-20-7  | 10 - 30  | *            |
| Aromatic 100                     | 64742-95-6 | 1 - 5    | *            |
| Butyl Acetate                    | 123-86-4   | 1 - 5    | *            |
| Ethyl Benzene                    | 100-41-4   | 1 - 5    | *            |
| Methyl Ethyl Ketone              | 78-93-3    | 1 - 5    | *            |
| Toluene                          | 108-88-3   | 1 - 5    | *            |
| Titanium dioxide                 | 13463-67-7 | 1 - 5    | *            |
| Stoddard Solvent                 | 8052-41-3  | 0.1 - 1  | *            |
| Cumene                           | 98-82-8    | 0.1 - 1  | *            |

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. FIRST AID MEASURES

##### Description of first aid measures

|   |  |
|---|--|
| <b>General advice</b>                     | If symptoms persist, call a physician. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing.  |
| <b>Eye contact</b>                        | Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician. Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician. |
| <b>Skin Contact</b>                       | Consult a physician if necessary. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Call a physician immediately.  |
| <b>Inhalation</b>                         | Remove to fresh air. Call a physician. If breathing is irregular or stopped, administer artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Move victim to fresh air. If not breathing, give artificial respiration. Call a physician immediately.                               |
| <b>Ingestion</b>                          | Do NOT induce vomiting. Rinse mouth. Drink plenty of water. If symptoms persist, call a physician. Drink 1 or 2 glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.  |
| <b>Self-protection of the first aider</b> | Use personal protective equipment as required.   |

##### Most important symptoms and effects, both acute and delayed

**Symptoms** No information available.

##### Indication of any immediate medical attention and special treatment needed

**Note to physicians** Treat symptomatically.

#### 5. FIRE-FIGHTING MEASURES

##### Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable extinguishing media** CAUTION: Use of water spray when fighting fire may be inefficient.

##### Specific hazards arising from the chemical

Flammable.

##### Explosion data

**Sensitivity to Mechanical Impact** None.

**Sensitivity to Static Discharge** None.

##### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

#### 6. ACCIDENTAL RELEASE MEASURES

##### Personal precautions, protective equipment and emergency procedures

**Personal precautions** Remove all sources of ignition. Use personal protective equipment as required.

##### Environmental precautions

**Environmental precautions** Prevent entry into waterways, sewers, basements or confined areas. Do not flush into surface water or sanitary sewer system. See Section 12 for additional ecological information.

#### Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up** Cover liquid spill with sand, earth or other non-combustible absorbent material. Cover powder spill with plastic sheet or tarp to minimize spreading. Pick up and transfer to properly labeled containers. Soak up with inert absorbent material.

## 7. HANDLING AND STORAGE

#### Precautions for safe handling

**Advice on safe handling** Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Wash contaminated clothing before reuse. Do not breathe dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product.

#### Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

**Incompatible materials** Strong oxidizing agents. Strong acids. Chlorinated compounds.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

#### Exposure Guidelines

| Chemical Name                  | ACGIH TLV                     | OSHA PEL   | NIOSH IDLH   |
|--------------------------------|-------------------------------|--|--|
| Xylene<br>1330-20-7            | STEL: 150 ppm<br>TWA: 100 ppm | TWA: 100 ppm<br>TWA: 435 mg/m <sup>3</sup><br>(vacated) TWA: 100 ppm<br>(vacated) TWA: 435 mg/m <sup>3</sup><br>(vacated) STEL: 150 ppm<br>(vacated) STEL: 655 mg/m <sup>3</sup> | -  |
| Butyl Acetate<br>123-86-4      | STEL: 200 ppm<br>TWA: 150 ppm | TWA: 150 ppm<br>TWA: 710 mg/m <sup>3</sup><br>(vacated) TWA: 150 ppm<br>(vacated) TWA: 710 mg/m <sup>3</sup><br>(vacated) STEL: 200 ppm<br>(vacated) STEL: 950 mg/m <sup>3</sup> | IDLH: 1700 ppm<br>TWA: 150 ppm<br>TWA: 710 mg/m <sup>3</sup><br>STEL: 200 ppm<br>STEL: 950 mg/m <sup>3</sup> |
| Ethyl Benzene<br>100-41-4      | TWA: 20 ppm                   | TWA: 100 ppm<br>TWA: 435 mg/m <sup>3</sup><br>(vacated) TWA: 100 ppm<br>(vacated) TWA: 435 mg/m <sup>3</sup><br>(vacated) STEL: 125 ppm<br>(vacated) STEL: 545 mg/m <sup>3</sup> | IDLH: 800 ppm<br>TWA: 100 ppm<br>TWA: 435 mg/m <sup>3</sup><br>STEL: 125 ppm<br>STEL: 545 mg/m <sup>3</sup>  |
| Methyl Ethyl Ketone<br>78-93-3 | STEL: 300 ppm<br>TWA: 200 ppm | TWA: 200 ppm<br>TWA: 590 mg/m <sup>3</sup><br>(vacated) TWA: 200 ppm<br>(vacated) TWA: 590 mg/m <sup>3</sup><br>(vacated) STEL: 300 ppm<br>(vacated) STEL: 885 mg/m <sup>3</sup> | IDLH: 3000 ppm<br>TWA: 200 ppm<br>TWA: 590 mg/m <sup>3</sup><br>STEL: 300 ppm<br>STEL: 885 mg/m <sup>3</sup> |
| Toluene<br>108-88-3            | TWA: 20 ppm                   | TWA: 200 ppm<br>(vacated) TWA: 100 ppm<br>(vacated) TWA: 375 mg/m <sup>3</sup><br>(vacated) STEL: 150 ppm<br>(vacated) STEL: 560 mg/m <sup>3</sup><br>Ceiling: 300 ppm           | IDLH: 500 ppm<br>TWA: 100 ppm<br>TWA: 375 mg/m <sup>3</sup><br>STEL: 150 ppm<br>STEL: 560 mg/m <sup>3</sup>  |

|                                |                           |  |   |
|--------------------------------|---------------------------|--|---|
| Titanium dioxide<br>13463-67-7 | TWA: 10 mg/m <sup>3</sup> | TWA: 15 mg/m <sup>3</sup> total dust<br>(vacated) TWA: 10 mg/m <sup>3</sup> total dust   | IDLH: 5000 mg/m <sup>3</sup>  |
| Stoddard Solvent<br>8052-41-3  | TWA: 100 ppm              | TWA: 500 ppm<br>TWA: 2900 mg/m <sup>3</sup><br>(vacated) TWA: 100 ppm<br>(vacated) TWA: 525 mg/m <sup>3</sup>                    | IDLH: 20000 mg/m <sup>3</sup><br>Ceiling: 1800 mg/m <sup>3</sup> 15 min<br>TWA: 350 mg/m <sup>3</sup> |
| Cumene<br>98-82-8              | TWA: 50 ppm               | TWA: 50 ppm<br>TWA: 245 mg/m <sup>3</sup><br>(vacated) TWA: 50 ppm<br>(vacated) TWA: 245 mg/m <sup>3</sup><br>(vacated) S*<br>S* | IDLH: 900 ppm<br>TWA: 50 ppm<br>TWA: 245 mg/m <sup>3</sup>  |

NIOSH IDLH *Immediately Dangerous to Life or Health*

**Other Information** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

**Appropriate engineering controls**

**Engineering Controls** Showers  
Eyewash stations  
Ventilation systems.

**Individual protection measures, such as personal protective equipment**

- Eye/face protection** Tight sealing safety goggles.
- Skin and body protection** No special technical protective measures are necessary.
- Respiratory protection** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

**General Hygiene Considerations** Handle in accordance with good industrial hygiene and safety practice.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Information on basic physical and chemical properties**

|                       |                          |                       |                          |
|-----------------------|--------------------------|-----------------------|--------------------------|
| <b>Physical state</b> | liquid                   | <b>Odor</b>           | No information available |
| <b>Appearance</b>     | No information available | <b>Odor threshold</b> | No information available |
| <b>Color</b>          | No information available |                       |                          |

| <u>Property</u>               | <u>Values</u>            | <u>Remarks • Method</u> |
|-------------------------------|--------------------------|-------------------------|
| pH                            | No information available |                         |
| Melting point/freezing point  | No information available |                         |
| Boiling point / boiling range | >= 79 °C / 174 °F        |                         |
| Flash point                   | -1 °C / 30 °F            |                         |
| Evaporation rate              | No information available |                         |
| Flammability (solid, gas)     | No information available |                         |
| Flammability Limit in Air     |                          |                         |
| Upper flammability limit:     | No information available |                         |
| Lower flammability limit:     | No information available |                         |
| Vapor pressure                | No information available |                         |
| Vapor density                 | No information available |                         |
| Specific Gravity              | 0.96                     |                         |
| Water solubility              | No information available |                         |
| Solubility in other solvents  | No information available |                         |
| Partition coefficient         | No information available |                         |
| Autoignition temperature      | No information available |                         |
| Decomposition temperature     | No information available |                         |

**Kinematic viscosity** No information available  
**Dynamic viscosity** No information available  
**Explosive properties** No information available  
**Oxidizing properties** No information available

**Other Information**

**Softening point** No information available  
**Molecular weight** No information available  
**VOC Content (%)** No information available  
**Density** 8.01 lbs/gal  
**Bulk density** No information available  
**Percent solids by weight** 41.0%  
**Percent volatile by weight** 59.0%  
**Percent solids by volume** 34.6%  
**Actual VOC (lbs/gal)** 4.7  
**Actual VOC (grams/liter)** 566.2  
**EPA VOC (lbs/gal)** 4.7  
**EPA VOC (grams/liter)** 566.2  
**EPA VOC (lb/gal solids)** 13.7

**10. STABILITY AND REACTIVITY**

**Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of Hazardous Reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Strong oxidizing agents. Strong acids. Chlorinated compounds.

**Hazardous Decomposition Products**

Carbon oxides.

**11. TOXICOLOGICAL INFORMATION**

**Information on likely routes of exposure**

**Product Information** No data available

**Inhalation** No data available.

**Eye contact** No data available.

**Skin Contact** No data available.

**Ingestion** No data available.

| Chemical Name                                  | Oral LD50            | Dermal LD50  | Inhalation LC50                                    |
|--|----------------------|--|--|
| Solvent Naphtha, Light Aliphatic<br>64742-89-8 | -                    | = 3000 mg/kg ( Rabbit )                            | -  |
| Xylene<br>1330-20-7                            | = 3500 mg/kg ( Rat ) | > 1700 mg/kg ( Rabbit ) > 4350<br>mg/kg ( Rabbit ) | = 29.08 mg/L ( Rat ) 4 h = 5000<br>ppm ( Rat ) 4 h |
| Aromatic 100<br>64742-95-6                     | = 8400 mg/kg ( Rat ) | > 2000 mg/kg ( Rabbit )                            | = 3400 ppm ( Rat ) 4 h                             |

|                                |   |   |  |
|--------------------------------|---|---|--|
| Butyl Acetate<br>123-86-4      | = 10768 mg/kg ( Rat )                     | > 17600 mg/kg ( Rabbit )                        | = 390 ppm ( Rat ) 4 h  |
| Ethyl Benzene<br>100-41-4      | = 3500 mg/kg ( Rat )                      | = 15400 mg/kg ( Rabbit )                        | = 17.2 mg/L ( Rat ) 4 h                                      |
| Methyl Ethyl Ketone<br>78-93-3 | = 2483 mg/kg ( Rat ) = 2737 mg/kg ( Rat ) | = 5000 mg/kg ( Rabbit ) = 6480 mg/kg ( Rabbit ) | = 11700 ppm ( Rat ) 4 h                                      |
| Toluene<br>108-88-3            | = 2600 mg/kg ( Rat )                      | = 12000 mg/kg ( Rabbit )                        | = 12.5 mg/L ( Rat ) 4 h                                      |
| Titanium dioxide<br>13463-67-7 | > 10000 mg/kg ( Rat )                     | -   | -  |
| Cumene<br>98-82-8              | = 1400 mg/kg ( Rat )                      | = 12300 µL/kg ( Rabbit )                        | = 39000 mg/m <sup>3</sup> ( Rat ) 4 h > 3577 ppm ( Rat ) 6 h |

**Information on toxicological effects**

**Symptoms** No information available.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization** No information available.

**Germ cell mutagenicity** No information available.

**Carcinogenicity** No information available.

| Chemical Name                  | ACGIH | IARC     | NTP                    | OSHA |
|--------------------------------|-------|----------|------------------------|------|
| Xylene<br>1330-20-7            | -     | Group 3  | -                      | -    |
| Ethyl Benzene<br>100-41-4      | A3    | Group 2B | -                      | X    |
| Toluene<br>108-88-3            | -     | Group 3  | -                      | -    |
| Titanium dioxide<br>13463-67-7 | -     | Group 2B | -                      | X    |
| Cumene<br>98-82-8              | -     | Group 2B | Reasonably Anticipated | X    |

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not classifiable as a human carcinogen

NTP (National Toxicology Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

**Reproductive toxicity** Product is or contains a chemical which is a known or suspected reproductive hazard.

**STOT - single exposure** No information available.

**STOT - repeated exposure** No information available.

**Chronic toxicity**

Contains a known or suspected reproductive toxin. Ethylbenzene has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B). Prolonged or repeated overexposure to ethylbenzene may result in adverse effects to the kidneys, liver, respiratory system, thyroid, testicles, and pituitary glands. May cause adverse liver effects.

**Target Organ Effects**

Central nervous system, Eyes, kidney, liver, lungs, Respiratory system, Skin.

**Aspiration hazard**

No information available.

**Numerical measures of toxicity - Product Information**

The following values are calculated based on chapter 3.1 of the GHS document mg/kg mg/l

**12. ECOLOGICAL INFORMATION****Ecotoxicity**

2.47% of the mixture consists of component(s) of unknown hazards to the aquatic environment

| Chemical Name                                  | Algae/aquatic plants                                    | Fish | Crustacea |
|--|---|------|-----------|
| Solvent Naphtha, Light Aliphatic<br>64742-89-8 | 4700: 72 h Pseudokirchneriella<br>subcapitata mg/L EC50 | -    | -         |

|                                |  |   |   |
|--------------------------------|--|---|---|
| Xylene<br>1330-20-7            | -  | 13.4: 96 h Pimephales promelas mg/L LC50 flow-through 2.661 - 4.093: 96 h Oncorhynchus mykiss mg/L LC50 static 13.5 - 17.3: 96 h Oncorhynchus mykiss mg/L LC50 13.1 - 16.5: 96 h Lepomis macrochirus mg/L LC50 flow-through 19: 96 h Lepomis macrochirus mg/L LC50 7.711 - 9.591: 96 h Lepomis macrochirus mg/L LC50 static 23.53 - 29.97: 96 h Pimephales promelas mg/L LC50 static 780: 96 h Cyprinus carpio mg/L LC50 semi-static 780: 96 h Cyprinus carpio mg/L LC50 30.26 - 40.75: 96 h Poecilia reticulata mg/L LC50 static | 3.82: 48 h water flea mg/L EC50<br>0.6: 48 h Gammarus lacustris mg/L LC50   |
| Aromatic 100<br>64742-95-6     | -  | 9.22: 96 h Oncorhynchus mykiss mg/L LC50  | 6.14: 48 h Daphnia magna mg/L EC50  |
| Butyl Acetate<br>123-86-4      | 674.7: 72 h Desmodesmus subspicatus mg/L EC50  | 100: 96 h Lepomis macrochirus mg/L LC50 static 17 - 19: 96 h Pimephales promelas mg/L LC50 flow-through 62: 96 h Leuciscus idus mg/L LC50 static  | 72.8: 24 h Daphnia magna mg/L EC50  |
| Ethyl Benzene<br>100-41-4      | 4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static | 11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 32: 96 h Lepomis macrochirus mg/L LC50 static 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static 9.6: 96 h Poecilia reticulata mg/L LC50 static  | 1.8 - 2.4: 48 h Daphnia magna mg/L EC50   |
| Methyl Ethyl Ketone<br>78-93-3 | -  | 3130 - 3320: 96 h Pimephales promelas mg/L LC50 flow-through  | 520: 48 h Daphnia magna mg/L EC50 5091: 48 h Daphnia magna mg/L EC50 4025 - 6440: 48 h Daphnia magna mg/L EC50 Static |
| Toluene<br>108-88-3            | 433: 96 h Pseudokirchneriella subcapitata mg/L EC50 12.5: 72 h Pseudokirchneriella subcapitata mg/L EC50 static  | 15.22 - 19.05: 96 h Pimephales promelas mg/L LC50 flow-through 12.6: 96 h Pimephales promelas mg/L LC50 static 5.89 - 7.81: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 14.1 - 17.16: 96 h Oncorhynchus mykiss mg/L LC50 static 5.8: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 11.0 - 15.0: 96 h Lepomis macrochirus mg/L LC50 static 54: 96 h Oryzias latipes mg/L LC50 static 28.2: 96 h Poecilia reticulata mg/L LC50 semi-static 50.87 - 70.34: 96 h Poecilia reticulata mg/L LC50 static                            | 5.46 - 9.83: 48 h Daphnia magna mg/L EC50 Static 11.5: 48 h Daphnia magna mg/L EC50                                   |
| Cumene<br>98-82-8              | 2.6: 72 h Pseudokirchneriella subcapitata mg/L EC50  | 6.04 - 6.61: 96 h Pimephales promelas mg/L LC50 flow-through 4.8: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 2.7: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 5.1: 96 h Poecilia reticulata mg/L LC50 semi-static   | 0.6: 48 h Daphnia magna mg/L EC50 7.9 - 14.1: 48 h Daphnia magna mg/L EC50 Static                                     |

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

| Chemical Name | Partition coefficient |
|---------------|-----------------------|
|---------------|-----------------------|



|                                |             |
|--------------------------------|-------------|
| Xylene<br>1330-20-7            | 2.77 - 3.15 |
| Butyl Acetate<br>123-86-4      | 1.81        |
| Ethyl Benzene<br>100-41-4      | 3.118       |
| Methyl Ethyl Ketone<br>78-93-3 | 0.29        |
| Toluene<br>108-88-3            | 2.65        |
| Cumene<br>98-82-8              | 3.55        |

**Other adverse effects** No information available

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Disposal of wastes** Disposal should be in accordance with applicable regional, national and local laws and regulations.

**Contaminated packaging** Do not reuse container.

**US EPA Waste Number** D001 U055 U159 U220 U239

| Chemical Name                  | RCRA | RCRA - Basis for Listing   | RCRA - D Series Wastes      | RCRA - U Series Wastes |
|--------------------------------|------|--|-----------------------------|------------------------|
| Xylene<br>1330-20-7            | -    | Included in waste stream:<br>F039  | -                           | U239                   |
| Ethyl Benzene<br>100-41-4      | -    | Included in waste stream:<br>F039  | -                           | -                      |
| Methyl Ethyl Ketone<br>78-93-3 | U159 | Included in waste streams:<br>F005, F039   | 200.0 mg/L regulatory level | U159                   |
| Toluene<br>108-88-3            | U220 | Included in waste streams:<br>F005, F024, F025, F039,<br>K015, K036, K037, K149,<br>K151 | -                           | U220                   |
| Cumene<br>98-82-8              | -    | -  | -                           | U055                   |

| Chemical Name       | RCRA - Halogenated Organic Compounds | RCRA - P Series Wastes | RCRA - F Series Wastes   | RCRA - K Series Wastes |
|---------------------|--------------------------------------|------------------------|--|------------------------|
| Toluene<br>108-88-3 | -                                    | -                      | Toxic waste<br>waste number F025<br>Waste description:<br>Condensed light ends, spent<br>filters and filter aids, and<br>spent desiccant wastes from<br>the production of certain<br>chlorinated aliphatic<br>hydrocarbons, by free<br>radical catalyzed processes.<br>These chlorinated aliphatic<br>hydrocarbons are those<br>having carbon chain lengths<br>ranging from one to and<br>including five, with varying<br>amounts and positions of<br>chlorine substitution. | -                      |

This product contains one or more substances that are listed with the State of California as a hazardous waste.

| Chemical Name       | California Hazardous Waste Status |
|---------------------|-----------------------------------|
| Xylene<br>1330-20-7 | Toxic<br>Ignitable                |

|                                |                    |
|--------------------------------|--------------------|
| Butyl Acetate<br>123-86-4      | Toxic              |
| Ethyl Benzene<br>100-41-4      | Toxic<br>Ignitable |
| Methyl Ethyl Ketone<br>78-93-3 | Toxic<br>Ignitable |
| Toluene<br>108-88-3            | Toxic<br>Ignitable |
| Cumene<br>98-82-8              | Toxic<br>Ignitable |

### 14. TRANSPORT INFORMATION

**DOT**

**UN/ID no.** UN1263  
**Proper shipping name** Paint  
**Hazard Class** Class 3, Flammable Liquid  
  
**Packing Group** II  
**Special Provisions** 149, B52, IB2, T4, TP1, TP8, TP28  
**Description** UN1263, Paint, Class 3, Flammable Liquid, II  
**Emergency Response Guide Number** 128

**TDG**

**UN/ID no.** UN1263  
**Proper shipping name** Paint  
**Hazard Class** 3  
**Packing Group** II  
**Description** UN1263, Paint, 3, II

**MEX**

**UN/ID no.** UN1263  
**Proper shipping name** Paint  
**Hazard Class** 3  
**Packing Group** II  
**Description** UN1263, Paint, 3, II

**ICAO (air)**

**UN/ID no.** UN1263  
**Proper shipping name** Paint  
**Hazard Class** 3  
**Packing Group** II  
**Special Provisions** A3, A72  
**Description** UN1263, Paint, 3, II

**IATA**

**UN/ID no.** UN1263  
**Proper shipping name** Paint  
**Hazard Class** 3  
**Packing Group** II  
**ERG Code** 3L  
**Special Provisions** A3, A72  
**Description** UN1263, Paint, 3, II

**IMDG**

**UN/ID no.** UN1263  
**Proper shipping name** Paint  
**Hazard Class** 3  
**Packing Group** II  
**EmS-No.** F-E, S-E  
**Special Provisions** 163

**Description** UN1263, Paint, 3, II

**RID**

**UN/ID no.** UN1263  
**Proper shipping name** Paint  
**Hazard Class** 3  
**Packing Group** II  
**Classification code** F1  
**Description** UN1263, Paint, 3, II

**ADR**

**UN/ID no.** UN1263  
**Proper shipping name** Paint  
**Hazard Class** 3  
**Packing Group** II  
**Classification code** F1  
**Tunnel restriction code** (D/E)  
**Special Provisions** 163, 640C, 650  
**Description** UN1263, Paint, 3, II, (D/E)  
**Labels** 3

**ADN**

**Proper shipping name** Paint  
**Hazard Class** 3  
**Packing Group** II  
**Classification code** F1  
**Special Provisions** 163, 640C, 650  
**Description** UN1263, Paint, 3, II  
**Hazard label(s)** 3  
**Limited quantity (LQ)** 5 L  
**Ventilation** VE01

**15. REGULATORY INFORMATION**

**International Inventories**

|                      |                   |
|----------------------|-------------------|
| <b>TSCA</b>          | Complies          |
| <b>DSL/NDSL</b>      | Complies *        |
| <b>EINECS/ELINCS</b> | Complies *        |
| <b>ENCS</b>          | Does not comply * |
| <b>IECSC</b>         | Complies *        |
| <b>KECL</b>          | Complies *        |
| <b>PICCS</b>         | Complies *        |
| <b>AICS</b>          | Complies *        |

\* This product contains an unknown chemical, therefore, this product's compliance to the inventory list is NOT DETERMINED

**Legend:**

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List  
**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**IECSC** - China Inventory of Existing Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances

**US Federal Regulations**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

|                      |                                      |
|----------------------|--------------------------------------|
| <b>Chemical Name</b> | <b>SARA 313 - Threshold Values %</b> |
|----------------------|--------------------------------------|

|                          |     |
|--------------------------|-----|
| Xylene - 1330-20-7       | 1.0 |
| Ethyl Benzene - 100-41-4 | 0.1 |
| Toluene - 108-88-3       | 1.0 |

**SARA 311/312 Hazard Categories**

|                                   |     |
|-----------------------------------|-----|
| Acute health hazard               | Yes |
| Chronic Health Hazard             | Yes |
| Fire hazard                       | Yes |
| Sudden release of pressure hazard | No  |
| Reactive Hazard                   | No  |

**CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

| Chemical Name             | CWA - Reportable Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants | CWA - Hazardous Substances |
|---------------------------|-----------------------------|------------------------|---------------------------|----------------------------|
| Xylene<br>1330-20-7       | 100 lb                      | -                      | -                         | X                          |
| Butyl Acetate<br>123-86-4 | 5000 lb                     | -                      | -                         | X                          |
| Ethyl Benzene<br>100-41-4 | 1000 lb                     | X                      | X                         | X                          |
| Toluene<br>108-88-3       | 1000 lb                     | X                      | X                         | X                          |

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

| Chemical Name                  | Hazardous Substances RQs | CERCLA/SARA RQ | Reportable Quantity (RQ)   |
|--------------------------------|--------------------------|----------------|--|
| Xylene<br>1330-20-7            | 100 lb                   | -              | RQ 100 lb final RQ<br>RQ 45.4 kg final RQ  |
| Butyl Acetate<br>123-86-4      | 5000 lb                  | -              | RQ 5000 lb final RQ<br>RQ 2270 kg final RQ   |
| Ethyl Benzene<br>100-41-4      | 1000 lb                  | -              | RQ 1000 lb final RQ<br>RQ 454 kg final RQ  |
| Methyl Ethyl Ketone<br>78-93-3 | 5000 lb                  | -              | RQ 5000 lb final RQ<br>RQ 2270 kg final RQ   |
| Toluene<br>108-88-3            | 1000 lb 1 lb             | -              | RQ 1000 lb final RQ<br>RQ 454 kg final RQ RQ 1 lb final RQ<br>RQ 0.454 kg final RQ |
| Cumene<br>98-82-8              | 5000 lb                  | -              | RQ 5000 lb final RQ<br>RQ 2270 kg final RQ   |

**US State Regulations**

**California Proposition 65**

This product contains the following Proposition 65 chemicals

| Chemical Name                 | California Proposition 65            |
|-------------------------------|--------------------------------------|
| Ethyl Benzene - 100-41-4      | Carcinogen                           |
| Toluene - 108-88-3            | Developmental<br>Female Reproductive |
| Titanium dioxide - 13463-67-7 | Carcinogen                           |
| Cumene - 98-82-8              | Carcinogen                           |

**U.S. State Right-to-Know Regulations**

| Chemical Name             | New Jersey | Massachusetts | Pennsylvania |
|---------------------------|------------|---------------|--------------|
| Xylene<br>1330-20-7       | X          | X             | X            |
| Butyl Acetate<br>123-86-4 | X          | X             | X            |
| Ethyl Benzene<br>100-41-4 | X          | X             | X            |

|                                       |   |   |   |
|---------------------------------------|---|---|---|
| Methyl Ethyl Ketone<br>78-93-3        | X | X | X |
| Toluene<br>108-88-3                   | X | X | X |
| Titanium dioxide<br>13463-67-7        | X | X | X |
| Cumene<br>98-82-8                     | X | X | X |
| Zinc 2-ethylhexanoic acid<br>136-53-8 | X | - | X |
| Zinc Napthanate<br>12001-85-3         | X | - | X |

**U.S. EPA Label Information**

**EPA Pesticide Registration Number** Not applicable

**Hazardous air pollutants (HAPS) content**

LIST OF HAZARDOUS AIR POLLUTANTS SUBJECT TO THE PROVISIONS OF THE CLEAN AIR ACT, TITLE I SECTION 112 'National Emission Standards for Hazardous Air Pollutants':

| Chemical Name             | Weight % of HAPS in Product | Pounds HAPS / Gal Product |
|---------------------------|-----------------------------|---------------------------|
| Xylene<br>1330-20-7       | 14.01%                      | 1.12                      |
| Ethyl Benzene<br>100-41-4 | 3.65%                       | 0.29                      |
| Toluene<br>108-88-3       | 2.90%                       | 0.23                      |

**16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION**

|             |                    |                |                    |                                    |
|-------------|--------------------|----------------|--------------------|------------------------------------|
| <b>NFPA</b> | Health hazards 2   | Flammability 3 | Instability 0      | Physical and Chemical Properties - |
| <b>HMIS</b> | Health hazards 2 * | Flammability 3 | Physical hazards 0 | Personal protection X              |

Chronic Hazard Star Legend      \* = Chronic Health Hazard

**Revision Date** 12-May-2015

**Revision Note**  
No information available

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Shipping information may vary based upon container size and shipping destination. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage, or release to the environment. The manufacturer assumes no responsibility for injury to the recipient or third persons, or for any damages to any property resulting from misuse of the product.

**End of Safety Data Sheet**