

# SAFETY DATA SHEET

Version 2

# 1. IDENTIFICATION

Product identifier

Product Name EZ Slide 80-20 Talc Graphite Powder

Other means of identification

Product Code 09011

**SKU(s)** 09011, 09012, 09014, 09018, S.143536, S.143537

Recommended use of the chemical and restrictions on use
Recommended Use
No information available.
Uses advised against
No information available

Details of the supplier of the safety data sheet

Manufacturer Address Van Sickle Paint Mfg. Co.

PO Box 82222 Lincoln, NE 68501 Phone: 402-476-6558 Fax: 402-476-6749

Emergency telephone number

Emergency Telephone Chemtrec 1-800-424-9300

### 2. HAZARDS IDENTIFICATION

#### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity	Category 1A
Combustible dust	Yes

### **Emergency Overview**

### Danger

#### Hazard statements

May cause cancer

May form combustible dust concentrations in air



Appearance powder Physical state Powder Odor No information available

#### **Precautionary Statements - Prevention**

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required

# **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

### **Precautionary Statements - Storage**

Store locked up

### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

### Hazards not otherwise classified (HNOC)

#### Other Information

· May form combustible dust concentrations in air

Unknown acute toxicity 0% of the mixture consists of ingredient(s) of unknown toxicity

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%	Trade Secret
Talc (powder)	14807-96-6	60 - 100	*
Graphite	7782-42-5	10 - 30	*
Crystalline Silica	14808-60-7	0.1 - 1	*

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

# 4. FIRST AID MEASURES

#### Description of first aid measures

Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Eye contact

Consult a physician.

**Skin Contact** Wash skin with soap and water.

Remove to fresh air. Inhalation

Ingestion Clean mouth with water and drink afterwards plenty of water.

# Most important symptoms and effects, both acute and delayed

No information available. **Symptoms** 

# Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

# 5. FIRE-FIGHTING MEASURES

### Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media CAUTION: Use of water spray when fighting fire may be inefficient.

#### Specific hazards arising from the chemical

Dusts or fumes may form explosive mixtures in air.

#### **Explosion data**

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge Fine dust dispersed in air, in sufficient concentrations, and in the presence of an ignition

source is a potential dust explosion hazard.

### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

# 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

**Personal precautions** Ensure adequate ventilation, especially in confined areas.

**Environmental precautions** 

**Environmental precautions** See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Use personal protective equipment as required. Cover powder spill with plastic sheet or tarp

to minimize spreading and keep powder dry. Take up mechanically, placing in appropriate containers for disposal. Avoid creating dust. Clean contaminated surface thoroughly.

# 7. HANDLING AND STORAGE

### Precautions for safe handling

Advice on safe handling Dust at sufficient concentrations can form explosive mixtures in air. Avoid the creation or

accumulation of dust when handling and keep away from all possible sources of ignition such as heat, sparks, and flame. Dust control and good housekeeping are required. Dust may carry a static charge. Make sure equipment and personnel are grounded to avoid static

discharge.

Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place.

Incompatible materials None known based on information supplied.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Talc (powder)	TWA: 2 mg/m³ particulate matter	(vacated) TWA: 2 mg/m³ respirable	IDLH: 1000 mg/m <sup>3</sup>
14807-96-6	containing no asbestos and <1%	dust <1% Crystalline silica,	TWA: 2 mg/m³ containing no
	crystalline silica, respirable	containing no Asbestos	Asbestos and <1% Quartz
	particulate matter	TWA: 20 mppcf if 1% Quartz or	respirable dust
		more;use Quartz limit	
Graphite	TWA: 2 mg/m³ respirable	TWA: 15 mg/m³ total dust synthetic	IDLH: 1250 mg/m <sup>3</sup>
7782-42-5	particulate matter all forms except	TWA: 5 mg/m³ respirable fraction	TWA: 2.5 mg/m³ natural respirable
	graphite fibers	synthetic	dust
		(vacated) TWA: 2.5 mg/m <sup>3</sup>	
		respirable dust natural	
		(vacated) TWA: 10 mg/m³ total dust	
		synthetic	
		(vacated) TWA: 5 mg/m³ respirable	
		fraction synthetic	
		TWA: 15 mppcf natural	
Crystalline Silica	TWA: 0.025 mg/m³ respirable	TWA: 50 μg/m³ TWA: 50 μg/m³	IDLH: 50 mg/m³ respirable dust
14808-60-7	particulate matter	excludes construction work,	TWA: 0.05 mg/m³ respirable dust
		agricultural operations, and	
		exposures that result from the	
		processing of sorptive clays	
		(vacated) TWA: 0.1 mg/m <sup>3</sup>	
		respirable dust	
		: (250)/(%SiO2 + 5) mppcf TWA	

respirable fraction
: (10)/(%SiO2 + 2) mg/m³ TWA
respirable fraction

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

**Eye/face protection** No special technical protective measures are necessary.

**Skin and body protection**No special technical protective measures are necessary.

**Respiratory protection** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

Remarks • Method

provided in accordance with current local regulations.

**General Hygiene Considerations** Handle in accordance with good industrial hygiene and safety practice.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Information on basic physical and chemical properties

Physical state Powder

AppearancepowderOdorNo information availableColorNo information availableOdor thresholdNo information available

<u>Property</u> <u>Values</u>

pH No information available
Melting point / freezing point
Boiling point / boiling range No information available
No information available

Flash point Not applicable

Evaporation rate
No information available
No information available
No information available

Flammability Limit in Air

Upper flammability limit:
Lower flammability limit:
Vapor pressure
Vapor density

No information available
No information available
No information available
No information available

Specific Gravity 2.64

Water solubility No information available Solubility in other solvents No information available **Partition coefficient** No information available **Autoignition temperature** No information available **Decomposition temperature** No information available Kinematic viscosity No information available **Dynamic viscosity** No information available No information available **Explosive properties Oxidizing properties** No information available

**Other Information** 

Softening point No information available Molecular weight No information available

Liquid Density 22.03 lbs/gal

Bulk density No information available

Percent solids by weight 100.0%
Percent volatile by weight 0.0%
Percent solids by volume 100.0%
Actual VOC (lbs/gal) 0
Actual VOC (grams/liter) 0
EPA VOC (grams/liter) 0
EPA VOC (grams/liter) 0
EPA VOC (lb/gal solids) 0

# 10. STABILITY AND REACTIVITY

#### Reactivity

No data available

#### **Chemical stability**

Stable under recommended storage conditions.

#### Possibility of hazardous reactions

None under normal processing.

#### Conditions to avoid

Extremes of temperature and direct sunlight.

### **Incompatible materials**

None known based on information supplied.

#### Hazardous decomposition products

None known based on information supplied.

# 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

Product Information No data available

**Inhalation** No data available.

Eye contact No data available.

**Skin Contact** No data available.

**Ingestion** No data available.

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Talc (powder) 14807-96-6	= 55,000 mg/kg (Rat)	-	-
Graphite 7782-42-5	> 9000 mg/kg (Rat)	-	-
Crystalline Silica 14808-60-7	> 22,500 mg/kg (Rat)	-	-

# Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** No information available.

# Delayed and immediate effects as well as chronic effects from short and long-term exposure

SensitizationNo information available.Germ cell mutagenicityNo information available.CarcinogenicityNo information available.

	Chemical name	ACGIH	IARC	NTP	OSHA
--	---------------	-------	------	-----	------

\_\_\_\_\_

Talc (powder) 14807-96-6	-	Group 3	-	Х
Crystalline Silica 14808-60-7	A2	Group 1	Known	Х

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 3 - Not classifiable as a human carcinogen

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity
STOT - single exposure
STOT - repeated exposure
No information available.
No information available.

Target organ effects Central Vascular System (CVS), Eyes, Respiratory system.

**Aspiration hazard** No information available.

### Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document mg/kg

# 12. ECOLOGICAL INFORMATION

### **Ecotoxicity**

20% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Crustacea
Talc (powder)	-	100: 96 h Brachydanio rerio g/L	-
14807-96-6		LC50 semi-static	

### Persistence and degradability

No information available.

#### **Bioaccumulation**

No information available.

Other adverse effects No information available

# 13. DISPOSAL CONSIDERATIONS

#### Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

**Contaminated packaging** Do not reuse container.

# 14. TRANSPORT INFORMATION

**DOT** Not regulated

# 15. REGULATORY INFORMATION

**International Inventories** 

**TSCA** Complies Complies **DSL/NDSL** Complies **EINECS/ELINCS ENCS** Does not comply **IECSC** Complies Complies **KECL PICCS** Complies **AICS** Complies

### Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

# **US Federal Regulations**

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

### SARA 311/312 Hazard Categories

Acute health hazard No
Chronic Health Hazard No
Fire hazard No
Sudden release of pressure hazard No
Reactive Hazard No

# **US State Regulations**

### **California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical name	California Proposition 65
Crystalline Silica - 14808-60-7	Carcinogen

#### U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts
Talc (powder)	X	X
14807-96-6		
Graphite	X	X
7782-42-5		
Crystalline Silica	X	X
14808-60-7		

Chemical name	Pennsylvania
Talc (powder) 14807-96-6	X
Graphite 7782-42-5	X

### U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

\_

# 16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 1 Flammability 0 Instability 0 Physical and chemical

properties -

HMIS Health hazards 1 \* Flammability 0 Physical hazards 0 Personal protection X

Chronic Hazard Star Legend \*= Chronic Health Hazard

Revision Date 03-Apr-2018

**Revision Note** 

No information available

**Disclaimer** 

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Shipping information may vary based upon container size and shipping destination. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage, or release to the environment. The manufacturer assumes no responsibility for injury to the recipient or third persons, or for any damages to any property resulting from misuse of the product.

**End of Safety Data Sheet**