

Revision Date 13-May-2015

SAFETY DATA SHEET

Version 1

1. IDENTIFICATION

Product identifier Product Name

AZ-2402 Aerosol High Temp. Aluminum

Other means of identification Product Code UN/ID no. SKU(s)

Recommended use of the chemical and restrictions on use			
Recommended Use	No information available.		
Uses advised against	No information available		

40270

None

UN1950

Details of the supplier of the safety data sheet

Manufacturer Address Van Sickle Paint Mfg. Co. PO Box 82222 Lincoln, NE 68501 Phone: 402-476-6558 Fax: 402-476-6749

Emergency telephone number Emergency Telephone

Chemtrec 1-800-424-9300

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration toxicity	Category 1
Flammable aerosols	Category 1

Emergency Overview

Danger

Hazard statements Causes serious eye irritation May cause genetic defects May cause cancer Causes damage to organs through prolonged or repeated exposure May be fatal if swallowed and enters airways Extremely flammable aerosol



Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Wash face, hands and any exposed skin thoroughly after handling Do not breathe dust/fume/gas/mist/vapors/spray Do not eat, drink or smoke when using this product

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other Information

Unknown acute toxicity

5.9% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%	Trade Secret
Propane	74-98-6	10 - 30	*
Acetone	67-64-1	10 - 30	*
Aliphatic Hydrocarbon	64742-49-0	7 - 13	*
Aluminum Powder	7429-90-5	7 - 13	*
Butane	106-97-8	7 - 13	*
Mineral Spirits	64742-48-9	5 - 10	*
Stoddard Solvent	8052-41-3	3 - 7	*
Solvent Naphtha, Medium Aliphatic	64742-88-7	1 - 5	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General adviceImmediate medical attention is required. In case of accident or unwellness, seek medical
advice immediately (show directions for use or safety data sheet if possible).Eye contactImmediately flush with plenty of water. After initial flushing, remove any contact lenses and
continue flushing for at least 15 minutes. Keep eye wide open while rinsing. Call a physician
immediately.

Skin Contact	Wash off immediately with plenty of water.			
Inhalation	Immediate medical attention is required. Remove to fresh air. If not breathing, give artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation.			
Ingestion	Do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. Drink plenty of water.			
Self-protection of the first aider	Remove all sources of ignition.			
Most important symptoms and effe	ects, both acute and delayed			
Symptoms	mptoms No information available.			
Indication of any immediate medical attention and special treatment needed				
Note to physicians	Treat symptomatically.			
5. FIRE-FIGHTING MEASURES				

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

No information available.

Explosion data Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

In the event of fire and/or explosion do not breathe fumes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions	Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate ventilation, especially in confined areas.			
Environmental precautions				
Environmental precautions	Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. See Section 12 for additional ecological information.			
Methods and material for containment and cleaning up				
Methods for containment	Prevent further leakage or spillage if safe to do so. Cover powder spill with plastic sheet or tarp to minimize spreading. Dike far ahead of liquid spill for later disposal.			
Methods for cleaning up	Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labeled containers.			
7. HANDLING AND STORAGE				

Precautions for safe handling

Advice on safe handling	Ensure adequate ventilation, especially in confined areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded. Avoid contact with eyes. Avoid breathing vapors or mists. Contents under pressure. Do not puncture or incinerate cans. Do not stick pin or any other sharp object into opening on top of can.
Conditions for safe storage, inc	luding any incompatibilities
Storage Conditions	Keep tightly closed in a dry and cool place. Keep in properly labeled containers.
Incompatible materials	Strong acids. Strong oxidizing agents. Chlorinated compounds.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Propane 74-98-6	: See Appendix F: Minimal Oxygen Content	TWA: 1000 ppm TWA: 1800 mg/m ³ (vacated) TWA: 1000 ppm	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³
		(vacated) TWA: 1800 mg/m ³	i tit i rooo mg, m
Acetone 67-64-1	STEL: 500 ppm TWA: 250 ppm	TWA: 1000 ppm TWA: 2400 mg/m ³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m ³ (vacated) STEL: 2400 mg/m ³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m ³
		in effect for all other sectors (vacated) STEL: 1000 ppm	
Aluminum Powder 7429-90-5	TWA: 1 mg/m ³ respirable fraction	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 5 mg/m ³ Al Aluminum	TWA: 10 mg/m³ total dust TWA: 5 mg/m³ respirable dust TWA: 5 mg/m³ Al
Butane 106-97-8	STEL: 1000 ppm	(vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m ³	TWA: 800 ppm TWA: 1900 mg/m ³
Stoddard Solvent 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m ³	IDLH: 20000 mg/m³ Ceiling: 1800 mg/m³ 15 min TWA: 350 mg/m³

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers Evewash

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection	Tight sealing safety goggles.
Skin and body protection	No special technical protective measures are necessary.

Respiratory protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.		
General Hygiene Considerations	When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended.		
	9. PHYSICAL AND CHEMICAL PROPERTIES		

Information on basic physical and chemical properties

Physical state Appearance Color	Aerosol No information available No information available	Odor Odor threshold	No information available No information available
Property pH Melting point/freezing point Boiling point / boiling range Flash point Evaporation rate Flammability (solid, gas) Flammability Limit in Air Upper flammability limit: Lower flammability limit: Vapor pressure Vapor density Specific Gravity Water solubility Solubility in other solvents Partition coefficient Autoignition temperature Decomposition temperature Kinematic viscosity Explosive properties Oxidizing properties	ValuesNo information available>= -42 °C / -43 °F-104 °C / -155 °FNo information availableNo	<u>Remarks • Method</u>	
Other Information Softening point Molecular weight VOC Content (%) Density Bulk density Percent solids by weight Percent volatile by weight Percent solids by volume Actual VOC (lbs/gal) Actual VOC (grams/liter) EPA VOC (lbs/gal) EPA VOC (lbs/gal) EPA VOC (grams/liter)	No information available No information available No information available 6.35 lbs/gal No information available 21.2% 61.1% 10.3% 3.9 465.5 4.7 560.8 37.6		

10. STABILITY AND REACTIVITY

Reactivity

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong acids. Strong oxidizing agents. Chlorinated compounds.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	No data available
Inhalation	No data available.
Eye contact	No data available.
Skin Contact	No data available.
Ingestion	No data available.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Propane 74-98-6	-	-	= 658 mg/L (Rat)4 h
Acetone 67-64-1	= 5800 mg/kg(Rat)	-	= 50100 mg/m³(Rat)8 h
Aliphatic Hydrocarbon 64742-49-0	> 5000 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 73680 ppm (Rat)4 h
Butane 106-97-8	-	-	= 658 g/m³ (Rat)4 h
Mineral Spirits 64742-48-9	> 5000 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	-
Solvent Naphtha, Medium Aliphatic 64742-88-7	> 5000 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	> 5.28 mg/L (Rat)4 h

Information on toxicological effects

Symptoms

No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure_

Sensitization	No information available.
Germ cell mutagenicity	No information available.
Carcinogenicity	No information available.
ACGIH (American Conference of Go	overnmental Industrial Hygienists)
A3 - Animal Carcinogen	
IARC (International Agency for Rese	earch on Cancer)
Group 3 - Not classifiable as a human	carcinogen
Reproductive toxicity	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Target Organ Effects	Central nervous system, Eyes, kidney, Respiratory system, Skin.
Aspiration hazard	No information available.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document mg/kg mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

57.69% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Acetone	-	4.74 - 6.33: 96 h Oncorhynchus	10294 - 17704: 48 h Daphnia
67-64-1		mykiss mL/L LC50 6210 - 8120: 96	magna mg/L EC50 Static 12600 -
		h Pimephales promelas mg/L LC50	12700: 48 h Daphnia magna mg/L
		static 8300: 96 h Lepomis	EC50
		macrochirus mg/L LC50	
Aliphatic Hydrocarbon	-	-	2.6: 96 h Chaetogammarus marinus
64742-49-0			mg/L LC50
Mineral Spirits	-	2200: 96 h Pimephales promelas	2.6: 96 h Chaetogammarus marinus
64742-48-9		mg/L LC50	mg/L LC50
Solvent Naphtha, Medium Aliphatic	450: 96 h Pseudokirchneriella	800: 96 h Pimephales promelas	100: 48 h Daphnia magna mg/L
64742-88-7	subcapitata mg/L EC50	mg/L LC50 static	EC50

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical Name	Partition coefficient
Propane 74-98-6	2.3
Acetone 67-64-1	-0.24
Butane 106-97-8	2.89

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastesDisposal should be in accordance with applicable regional, national and local laws and
regulations.Contaminated packagingDo not reuse container.

US EPA Waste Number

U002 U239

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Acetone	-	Included in waste stream:	-	U002
67-64-1		F039		

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
Acetone 67-64-1	Ignitable
Aluminum Powder 7429-90-5	Ignitable powder

14. TRANSPORT INFORMATION

DOT UN/ID no. Proper shipping name Hazard Class Description Emergency Response Guide Number	UN1950 Aerosols 2.1 UN1950, Aerosols, 2.1 126
<u>TDG</u> UN/ID no. Proper shipping name Hazard Class Description	UN1950 Aerosols 2.1 UN1950, Aerosols, 2.1
<u>MEX</u> UN/ID no. Proper shipping name Hazard Class Description	UN1950 Aerosols 2 UN1950, Aerosols, 2
ICAO (air) UN/ID no. Proper shipping name Hazard Class Special Provisions Description	UN1950 Aerosols 2.1 A145, A167 UN1950, Aerosols, 2.1
IATA UN/ID no. Proper shipping name Hazard Class ERG Code Special Provisions Description	UN1950 Aerosols, flammable 2.1 10L A145, A167, A802 UN1950, Aerosols, flammable, 2.1
IMDG UN/ID no. Proper shipping name Hazard Class EmS-No. Special Provisions Description	UN1950 Aerosols 2 F-D, S-U 63,190, 277, 327, 344, 959 UN1950, Aerosols, 2
<u>RID</u> UN/ID no. Proper shipping name Hazard Class Classification code Description	UN1950 Aerosols 2.1 5F UN1950, Aerosols, 2.1
ADR UN/ID no. Proper shipping name Hazard Class Classification code Tunnel restriction code Special Provisions Description Labels	UN1950 Aerosols 2.1 5F (D) 190, 327, 344, 625 UN1950, Aerosols, 2.1, (D) 2.1
ADN Proper shipping name	Aerosols

Hazard Class	2.1
Classification code	5F
Special Provisions	190, 327, 344, 625
Description	UN1950, Aerosols, 2.1
Hazard label(s)	2.1
Limited quantity (LQ)	1 L
Ventilation	VE01, VE04

15. REGULATORY INFORMATION

International Inventories	
TSCA	Complies
DSL/NDSL	Complies *
EINECS/ELINCS	Complies *
ENCS	Does not comply
IECSC	Complies *
KECL	Complies *
PICCS	Complies *
AICS	Complies *

* This product contains an unknown chemical, therefore, this product's compliance to the inventory list is NOT DETERMINED

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
Aluminum Powder - 7429-90-5	1.0

SARA 311/312 Hazard Categories

Acute health hazard	No
Chronic Health Hazard	Yes
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Acetone	5000 lb	-	RQ 5000 lb final RQ
67-64-1			RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Ethyl Benzene - 100-41-4	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Propane 74-98-6	Х	X	Х
Acetone 67-64-1	Х	X	Х
Aluminum Powder 7429-90-5	Х	X	Х
Butane 106-97-8	Х	X	Х
Stoddard Solvent 8052-41-3	Х	X	Х
Solvent Naphtha, Medium Aliphatic 64742-88-7	Х	-	-
Ethylene Glycol Butyl Ether 111-76-2	Х	X	Х
Propylene Glycol Methyl Ether 107-98-2	Х	X	Х
1,2,4-Trimethylbenzene 95-63-6	Х	Х	Х
Xylene 1330-20-7	Х	X	Х
Ethyl Benzene 100-41-4	Х	X	Х
Cobalt 2-ethylhexanoate 136-52-7	Х	-	Х

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

Hazardous air pollutants (HAPS) content

This product contains no reportable Hazardous Air Pollutants

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

Flammability 4

NFPA	
HMIS	

Health hazards 2*

Health hazards 2

Flammability 4

Physical hazards 0

Instability 0

Physical and Chemical Properties * Personal protection X

Chronic Hazard Star Legend

13-May-2015

* = Chronic Health Hazard

Revision Date Revision Note

No information available

Disclaimer

Discialmer The information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Shipping information may vary based upon container size and shipping destination. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage, or release to the environment. The manufacturer assumes no responsibility for injury to the recipient or third persons, or for any damages to any property resulting from misuse of the product.

End of Safety Data Sheet