

Revision date 17-Apr-2025

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: US OSHA Hazard Communication Standard (29 CFR 1910.1200)

Version 12

1. Identification		
Product identifier		
Product Name	T&E Enamel Gloss Ford Red	
Other means of identification		
Product Code(s)	48074	
Synonyms	None	
Recommended use of the chemical and restrictions on use		
Recommended Use	No information available	
Restrictions on use	No information available	
Details of the supplier of the safety data sheet		
Manufacturer Address Van Sickle 1020 Albany Place SE Orange City, IA 51041 Phone: (712) 737-4993 Fax: (712) 737-4997		
Emergency telephone number		

Emergency Telephone

Chemtrec 1-800-424-9300

2. Hazard(s) identification

Classification

Flammable liquids	Category 3
Skin sensitization	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Reproductive toxicity	Category 1B
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration hazard	Category 1

Hazards not otherwise classified (HNOC)

Not applicable

Label elements



Danger

Hazard statements

Flammable liquid and vapor. May cause an allergic skin reaction. May cause genetic defects. May cause cancer. May damage fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways.

Precautionary Statements - Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Contaminated work clothing must not be allowed out of the workplace. Do not breathe dust/fume/gas/mist/vapors/spray. Wash face, hands and any exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Use explosion-proof electrical/ ventilating/ lighting/ equipment.

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting. In case of fire: Use CO2, dry chemical, or foam to extinguish.

Precautionary Statements - Storage

Store locked up. Store in a well-ventilated place. Keep cool.

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant.

Other information

Causes mild skin irritation. Harmful to aquatic life with long lasting effects.

3. Composition/information on ingredients

Substance

Not applicable.

<u>Mixture</u>

Chemical name	CAS No.	Weight-%	Trade secret
---------------	---------	----------	--------------

48074 - T&E Enamel Gloss Ford Red

Solvent Naphtha, Medium Aliphatic	64742-88-7	35 to <50	*
Calcium Carbonate	471-34-1	5 to <10	*
Xylene	1330-20-7	1 to <5	*
Ethyl Benzene	100-41-4	0.1 to <1	*
Titanium dioxide	13463-67-7	0.1 to <1	*
Methyl Ethyl Ketoxime	96-29-7	0.1 to <1	*
Zirconium octoate	22464-99-9	0.1 to <1	*
Cobalt 2-ethylhexanoate	136-52-7	0.1 to <1	*
Mineral Spirits	64742-48-9	0.1 to <1	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures

Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention. Immediate medical attention is required.	
Inhalation	Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Remove to fresh air. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Get immediate medical attention. Delayed pulmonary edema may occur.	
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area.	
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a physician.	
Ingestion	ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. Do NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Rinse mouth. Never give anything by mouth to an unconscious person. Get immediate medical attention.	
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation.	
Most important symptoms and effects, both acute and delayed		
Symptoms	Itching. Rashes. Hives. Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Prolonged contact may cause redness and irritation.	
Effects of Exposure	May cause cancer. May cause adverse reproductive effects - such as birth defect, miscarriages, or infertility. Mutagenic effects. Causes damage to organs through prolonged or repeated exposure.	
Indication of any immediate medical attention and special treatment needed		
Note to physicians	May cause sensitization in susceptible persons. Treat symptomatically. Because of the danger of aspiration, emesis or gastric lavage should not be employed unless the risk is justified by the presence of additional toxic substances.	

5. Fire-fighting measures

a Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.

Large Fire	CAUTION: Use of water spray when fighting fire may be inefficient.	
Unsuitable extinguishing media	Do not scatter spilled material with high pressure water streams.	
Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Product is or contains a sensitizer. May cause sensitization by skin contact.	
Explosion data Sensitivity to mechanical impac	t None.	
Sensitivity to static discharge	Yes.	
Special protective equipment and precautions for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.	

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions	Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.
Other information	Ventilate the area. Refer to protective measures listed in Sections 7 and 8.
Methods and material for containme	ent and cleaning up
Methods for containment	Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.
Methods for cleaning up	Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

7. Handling and storage

Precautions for safe handling

Advice on safe handling	Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Remove contaminated clothing and shoes.
Conditions for safe storage, ir	cluding any incompatibilities

Storage ConditionsKeep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat,
sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static
electricity). Keep in properly labeled containers. Do not store near combustible materials.

Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children. Store away from other materials.

8. Exposure controls/personal protection

Control Parameters

Exposure Limits

The following ingredients are the only ingredients of the product above the cut-off level (or level that contributes to the hazard classification of the mixture) which have an exposure limit applicable in the region for which this safety data sheet is intended or other recommended limit. At this time, the other relevant constituents have no known exposure limits from the sources listed here.

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Calcium Carbonate 471-34-1	-	-	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
Xylene 1330-20-7	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³	
Ethyl Benzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³
Titanium dioxide 13463-67-7	TWA: 0.2 mg/m ³ nanoscale respirable particulate matter TWA: 2.5 mg/m ³ finescale respirable particulate matter	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction	IDLH: 5000 mg/m ³ TWA: 2.4 mg/m ³ CIB 63 fine TWA: 0.3 mg/m ³ CIB 63 ultrafine, including engineered nanoscale
Zirconium octoate 22464-99-9	STEL: 10 mg/m³ Zr TWA: 5 mg/m³ Zr	TWA: 5 mg/m ³ Zr (vacated) TWA: 5 mg/m ³ Zr (vacated) STEL: 10 mg/m ³ Zr	IDLH: 25 mg/m ³ Zr TWA: 5 mg/m ³ except Zirconium tetrachloride Zr STEL: 10 mg/m ³ Zr

Biological occupational exposure limits

Chemical name	ACGIH
	0.3 g/g creatinine - urine (total of all isomers of Methylhippuric acids) - end of shift
	150 mg/g creatinine - urine (Sum of mandelic acid and phenylglyoxylic acid) - end of shift

Appropriate engineering controls

Engineering controls	Showers Eyewash stations Ventilation systems.	
Individual protection measures, such as personal protective equipment		
Eye/face protection	Tight sealing safety goggles.	
Hand protection	Wear suitable gloves. Impervious gloves.	

Skin and body protection	Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Antistatic boots.
Respiratory protection	No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.
General hygiene considerations	Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

9. Physical and chemical properties

Information on basic physical and o	hemical properties	
Physical state	Liquid	
Appearance	No information available	
Color	No information available	
Odor	No information available	
Odor threshold	No information available	
Property_	Values	Remarks • Method
H	No data available	None known
pH (as aqueous solution)		None known
Melting point / freezing point	No data available	None known
Initial boiling point and boiling rang		None known
Flash point	37.8 °C / 100.0 °F	None known
Evaporation rate	No data available	None known
Flammability	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive	No data available	
limits		
Lower flammability or explosive	No data available	
limits	No uala avaliable	
	No data available	None known
Vapor pressure Relative vapor density	No data available	None known
Relative density	0.98	None known
	0.00	
Water solubility	No data available	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature		None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known
Other information		
Explosive properties	No information available	
Oxidizing properties	No information available	
Softening point	No information available	
Molecular weight	No information available	
VOC content	No information available	
Liquid Density	8.15 lbs/gal	
Bulk density	No information available	
Percent solids by weight	54.0%	
Percent volatile by weight	46.0%	
Percent volatile by weight Percent solids by volume	40.0%	
Actual VOC (lbs/gal)	42.3% 3.8	
Actual VOC (lbs/gal) Actual VOC (grams/liter)	3.0 449	
EPA VOC (Ibs/gal)	3.8	
EPA VOC (lbs/gal) EPA VOC (grams/liter)	3.0 449	
EFA VOC (grains/iller)	11 3	

10. Stability and reactivity

Reactivity	No information available.
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	None under normal processing.
Conditions to avoid	Heat, flames and sparks.
Incompatible materials	None known based on information supplied.

Hazardous decomposition products None known based on information supplied.

11. Toxicological information

Information on likely routes of exposure

Product Information

Inhalation	Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract.
Eye contact	Specific test data for the substance or mixture is not available. May cause irritation.
Skin contact	May cause sensitization by skin contact. Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). Repeated exposure may cause skin dryness or cracking. Causes mild skin irritation.
Ingestion	Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways.
Symptoms related to the physical, o	chemical and toxicological characteristics
Symptoms	Itching. Rashes. Hives. Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Prolonged contact may cause redness and irritation.
Acute toxicity	

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	14,632.90 mg/kg
ATEmix (dermal)	6,215.70 mg/kg
ATEmix (inhalation-dust/mist)	13.70 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Solvent Naphtha, Medium Aliphatic 64742-88-7	> 25 mL/kg (Rat)	> 4000 mg/kg (Rabbit)	> 5.28 mg/L (Rat)4 h
Calcium Carbonate 471-34-1	= 6450 mg/kg (Rat)	> 2000 mg/kg (Rat)	> 3 mg/L (Rat)4 h
Xylene 1330-20-7	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat)4 h
Ethyl Benzene 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.4 mg/L (Rat)4 h
Titanium dioxide 13463-67-7	> 2000 mg/kg (Rat)	-	> 5.09 mg/L (Rat)4 h

Methyl Ethyl Ketoxime 96-29-7	= 930 mg/kg (Rat)	1000 - 1800 mg/kg (Rabbit)	> 4.83 mg/L (Rat)4 h
Zirconium octoate 22464-99-9	> 5000 mg/kg (Rat)	-	-
Cobalt 2-ethylhexanoate 136-52-7	= 1300 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	> 10 mg/L (Rat)1 h
Mineral Spirits 64742-48-9	> 6000 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	> 8500 mg/m³(Rat)4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Classification based on data available for ingredients. Causes mild skin irritation.
Serious eye damage/eye irritation	No information available.
Respiratory or skin sensitization	May cause an allergic skin reaction.
Germ cell mutagenicity	Contains a known or suspected mutagen. Classification based on data available for ingredients. May cause genetic defects.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Xylene 1330-20-7	-	Group 3	-	-
Ethyl Benzene 100-41-4	A3	Group 2B	-	Х
Titanium dioxide 13463-67-7	A3	Group 2B	-	Х
Cobalt 2-ethylhexanoate 136-52-7	-	Group 2B Group 3	Reasonably Anticipated	Х

Legend

ACGIH (American Conference of Governmental Industrial Hygienists) A3 - Animal Carcinogen IARC (International Agency for Research on Cancer) Group 2B - Possibly Carcinogenic to Humans Group 3 - Not Classifiable as to Carcinogenicity in Humans NTP (National Toxicology Program) Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen OSHA (Occupational Safety and Health Administration of the US Department of Labor) X - Present

Reproductive toxicity	Classification based on data available for ingredients. May damage fertility or the unborn child.
STOT - single exposure	No information available.
STOT - repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Target organ effects	Respiratory system, Eyes, Skin.
Aspiration hazard	May be fatal if swallowed and enters airways.

Other adverse effects No information available.

Interactive effects

No information available.

12. Ecological information

Ecotoxicity

Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to	Crustacea
			microorganisms	
Solvent Naphtha, Medium	450: 96 h	800: 96 h Pimephales	-	100: 48 h Daphnia
Aliphatic	Pseudokirchneriella	promelas mg/L LC50		magna mg/L EC50
64742-88-7	subcapitata mg/L EC50			
Xylene	-	13.4: 96 h Pimephales	-	3.82: 48 h water flea
1330-20-7		promelas mg/L LC50		mg/L EC50
		flow-through		0.6: 48 h Gammarus
		2.661 - 4.093: 96 h		lacustris mg/L LC50
		Oncorhynchus mykiss		
		mg/L LC50 static		
		13.5 - 17.3: 96 h		
		Oncorhynchus mykiss		
		mg/L LC50		
		13.1 - 16.5: 96 h		
		Lepomis macrochirus		
		mg/L LC50 flow-through		
		19: 96 h Lepomis		
		macrochirus mg/L LC50		
		7.711 - 9.591: 96 h		
		Lepomis macrochirus		
		mg/L LC50 static		
		23.53 - 29.97: 96 h		
		Pimephales promelas		
		mg/L LC50 static		
		780: 96 h Cyprinus		
		carpio mg/L LC50		
		semi-static		
		780: 96 h Cyprinus		
		carpio mg/L LC50		
		30.26 - 40.75: 96 h		
		Poecilia reticulata mg/L		
	4.0.701	LC50 static		
Ethyl Benzene	4.6: 72 h	11.0 - 18.0: 96 h	-	1.8 - 2.4: 48 h Daphnia
100-41-4	Pseudokirchneriella	Oncorhynchus mykiss		magna mg/L EC50
	subcapitata mg/L EC50	mg/L LC50 static		
		4.2: 96 h Oncorhynchus		
	Pseudokirchneriella	mykiss mg/L LC50		
	subcapitata mg/L EC50			
	2.6 - 11.3: 72 h Pseudokirchneriella	7.55 - 11: 96 h		
		Pimephales promelas mg/L LC50 flow-through		
		°		
	static 1.7 - 7.6: 96 h	32: 96 h Lepomis macrochirus mg/L LC50		
	Pseudokirchneriella	static		
	subcapitata mg/L EC50			
	static	Pimephales promelas		
	510110	mg/L LC50 static		
		9.6: 96 h Poecilia		
		reticulata mg/L LC50		
		static		
Methyl Ethyl Ketoxime	83: 72 h Desmodesmus	777 - 914: 96 h	_	750: 48 h Daphnia

96-29-7	subspicatus mg/L EC50	Pimephales promelas mg/L LC50 flow-through 760: 96 h Poecilia reticulata mg/L LC50		magna mg/L EC50
		static		
Mineral Spirits	-	2200: 96 h Pimephales	-	-
64742-48-9		promelas mg/L LC50		

Persistence and degradability

No information available.

Bioaccumulation

Component Information

Chemical name	Partition coefficient	
Xylene	2.77 - 3.15	
1330-20-7		
Ethyl Benzene	3.6	
100-41-4		
Methyl Ethyl Ketoxime	0.65	
96-29-7		

Other adverse effects

No information available.

13. Disposal considerations

Disposal methods

Waste from residues/unused products	Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.
California Hazardous Waste Status	This product contains one or more substances that are listed with the State of California as a hazardous waste.

14. Transport information

DOT

Not regulated

15. Regulatory information

International Inventories

TSCA

Complies

*Contact supplier for details. One or more substances in this product are either not listed on the US TSCA inventory, listed on the confidential US TSCA inventory or are otherwise exempted from inventory listing requirements

DSL/NDSL EINECS/ELINCS Complies Contact supplier for inventory compliance status.

ENCS	Contact supplier for inventory compliance status.
IECSC	
KECL	Contact supplier for inventory compliance status.
PICCS	Contact supplier for inventory compliance status.
AIIC	Contact supplier for inventory compliance status.
NZIOC	Contact supplier for inventory compliance status.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

- PICCS Philippines Inventory of Chemicals and Chemical Substances
- AICS Australian Inventory of Chemical Substances

NZIOC - New Zealand Inventory of Chemicals

US Federal Regulations

<u>SARA 313</u>

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	SARA 313 - Threshold Values %	
Xylene - 1330-20-7	1.0	
Ethyl Benzene - 100-41-4	0.1	
Cobalt 2-ethylhexanoate - 136-52-7	0.1	

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylene 1330-20-7	100 lb	-	-	Х
Ethyl Benzene 100-41-4	1000 lb	Х	Х	Х

<u>CERCLA</u>

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	Reportable Quantity (RQ)
Xylene 1330-20-7	100 lb	-	RQ 100 lb final RQ RQ 45.4 kg final RQ
Ethyl Benzene 100-41-4	1000 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:.

Chemical name	California Proposition 65	
Hansa Orange (Orange 5) - 3468-63-1	Carcinogen	
Ethyl Benzene - 100-41-4	Carcinogen	

Titanium dioxide - 13463-67-7	Carcinogen
Crystalline Silica - 14808-60-7	Carcinogen
Naphthalene - 91-20-3	Carcinogen
Cumene - 98-82-8	Carcinogen
Toluene - 108-88-3	Developmental
Benzene(including benzene from gasoline) - 71-43-2	Carcinogen
	Developmental
	Male Reproductive
Mercury - 7439-97-6	Developmental
Nickel - 7440-02-0	Carcinogen
Cobalt - 7440-48-4	Carcinogen
Lead Chromate - 7758-97-6	Carcinogen
	Developmental
	Female Reproductive
	Male Reproductive
Cadmium - 7440-43-9	Carcinogen
	Developmental
	Male Reproductive

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Xylene 1330-20-7	Х	X	Х
Ethyl Benzene 100-41-4	х	X	Х
Titanium dioxide 13463-67-7	Х	X	Х
1,2,4-Trimethylbenzene 95-63-6	Х	X	Х
Cobalt 2-ethylhexanoate 136-52-7	Х	-	Х
Crystalline Silica 14808-60-7	Х	X	Х
Diethylene Glycol Methyl Ether 111-77-3	Х	X	Х
Aluminum oxide 1344-28-1	Х	X	Х
Iron (III) oxide, as Fe 1309-37-1	Х	-	Х
Trimanganese tetraoxide 1317-35-7	Х	X	Х
Kaolin 1332-58-7	Х	X	Х
Stoddard Solvent 8052-41-3	Х	X	Х
Nonane 111-84-2	Х	X	Х
Oleic acid 112-80-1	-	-	Х
Calcium carbonate 1317-65-3	Х	X	Х
Propylene Glycol Methyl Ether 107-98-2	Х	X	Х
Diethylene Glycol Butyl Ether 112-34-5	Х	-	Х
Propionic Acid 79-09-4	Х	X	Х
2-Ethylhexanoic acid 149-57-5	Х	-	-
Naphthalene	Х	Х	Х

91-20-3			
Cumene 98-82-8	Х	X	Х
Toluene 108-88-3	Х	X	Х
Chromium 7440-47-3	Х	X	Х
Benzene(including benzene from gasoline) 71-43-2	Х	X	Х
Arsenic 7440-38-2	Х	X	Х
Cobalt 7440-48-4	Х	X	Х
Mercury 7439-97-6	Х	X	Х
Nickel 7440-02-0	Х	X	Х
Phosphoric Acid 7664-38-2	Х	X	Х
Lead Chromate 7758-97-6	Х	X	Х
Cadmium 7440-43-9	Х	X	Х

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

LIST OF HAZARDOUS AIR POLLUTANTS SUBJECT TO THE PROVISIONS OF THE CLEAN AIR ACT, TITLE I SECTION 112 'National Emission Standards for Hazardous Air Pollutants' (present if listed in Section 3):

Chemical name	Weight % of HAPS in Product	Pounds HAPS / Gal Product
Xylene	2.42	0.20
1330-20-7		
Ethyl Benzene	0.42	0.03
100-41-4		
Cobalt 2-ethylhexanoate	0.24	0.02
136-52-7		

16. Other infor	mation			
NFPA <u>HMIS</u> Chronic Hazard Star Le	Health hazards 2 Health hazards 2 * egend *= Chronic H	Flammability 2 Flammability 2 Health Hazard	Instability 0 Physical hazards 0	Special hazards - Personal protection X
Key or legend to ab	breviations and acronyms u	used in the safety data	<u>sheet</u>	
Legend Section 8:	Exposure controls/personal	protection		
TWA T	WA (time-weighted average)	STEL	STEL (Short Tern	n Exposure Limit)
Ceiling N	/laximum limit value	*	Skin designation	
+ S	Sensitizers			
Agency for Toxic Sub U.S. Environmental F European Food Safe Environmental Protect Acute Exposure Guid U.S. Environmental F U.S. Environmental F Food Research Journ Hazardous Substance International Uniform	ction Agency deline Level(s) (AEGL(s)) Protection Agency Federal Ins Protection Agency High Produc nal	y (ATSDR) Database ecticide, Fungicide, and ction Volume Chemicals ase (IUCLID)	Rodenticide Act	

Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS) NIOSH (National Institute for Occupational Safety and Health) National Library of Medicine's ChemID Plus (NLM CIP) National Library of Medicine's PubMed database (NLM PUBMED) U.S. National Toxicology Program (NTP) New Zealand's Chemical Classification and Information Database (CCID) Organization for Economic Co-operation and Development Environment, Health, and Safety Publications Organization for Economic Co-operation and Development High Production Volume Chemicals Program Organization for Economic Co-operation and Development Screening Information Data Set World Health Organization

Revision date	17-Apr-2025
Revision Note	No information available.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet