

**Clear Hardener**

IPDI Urethane Additive

California VOC Restricted Product
**Product Data Sheet**
**PRODUCT DESCRIPTION:**

Ideal® Clear Hardener/Catalyst is an IPDI Urethane hardener used to enhance cure, gloss hardness and abrasion resistance.

**TYPICAL USES:**

Ideal® Clear Hardener/Catalyst may be used in Ideal® Tractor and Equipment enamel. Not recommended for use in Metallic, or Aluminum coatings.

**NOT FOR SALE IN CALIFORNIA**
**BASES & COLORS:**

Clear liquid additive.

**SURFACE PREPARATION:**

Ideal® Clear Hardener/Catalyst is an additive. Follow label directions on coating label.

**APPLICATION:**

N/A

**SAFETY PRECAUTIONS:**

Contains aliphatic polyisocyanate of isophorone diisocyanate and butyl acetate. Proper skin and supplied air respiratory protection is recommended. Refer to Material Safety Data sheets for information.

The contents of 7016 will be blended with other components, having the hazards of all components.

**ENVIRONMENTAL VARIABLES:**

Will vary on what product this additive is used in. Please see data sheet for the base product this will be added to.

**Dry-Times:**

N/A

**CLEAN-UP:**

Clean with an enamel reducer approved for use in your air quality district.

**PHYSICAL PROPERTIES:**

PRODUCT NUMBER:	7016
GENERAL TYPE:	Hardener/ Catalyst
COLOR:	Clear
SOLIDS BY WEIGHT:	49.3%
SOLIDS BY VOLUME:	42.2%
THEORETICAL COVERAGE @ 1 MIL DFT:	N/A
RECOMMENDED DFT:	N/A
VISCOSITY @ 78°F:	85-100 KU
WEIGHT PER GALLON:	8.3 lbs.
FLASH POINT:	85°F
VOC:	507 G/L

**Clear Hardener**

IPDI Urethane Additive

California VOC Restricted Product**Product Data Sheet**

---

**CAUTIONS:**

For exterior use only,

Do not take internally,

Use with adequate ventilation,

KEEP OUT OF REACH OF CHILDREN

\*WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the national Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

For additional Product Information or Safety Data Sheets, please call 800-677-2468, 8:00-5:00 CST Mon.-Fri.

**Limited Warranty:**

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since Van Sickle®Paint does not control the application of its products, or the condition of the surfaces to which they are applied, Van Sickle®Paint's liability will under no circumstances exceed replacement of the product.