

Revision Date 12-May-2015

SAFETY DATA SHEET

Version 2

1. IDENTIFICATION

Product	identifier
Product	Name

Flat White/Pastel Base Finish

Other means of identificationProduct Code71035SKU(s)71031, 71035

Recommended use of the chemical and restrictions on useRecommended UseNo information available.Uses advised againstNo information available

Details of the supplier of the safety data sheet

Manufacturer Address

Van Sickle Paint Mfg. Co. PO Box 82222 Lincoln, NE 68501 Phone: 402-476-6558 Fax: 402-476-6749

Emergency telephone number Emergency Telephone

Chemtrec 1-800-424-9300

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity Category 1B Emergency Overview Danger Hazard statements May cause cancer Appearance No information available Physical state liquid Odor No information available Precautionary Statements - Prevention Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other Information

Harmful to aquatic life with long lasting effects

• Harmful to aquatic life Unknown acute toxicity

ty 9.93% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%	Trade Secret
Titanium dioxide	13463-67-7	10 - 30	*
Kaolin	1332-58-7	5 - 10	*
Barium metaborate monohydrate	13701-59-2	1 - 5	*
Ethylene Glycol	107-21-1	1 - 5	*
Zinc oxide, as Zn (fume)	1314-13-2	0.1 - 1	*
Heavy Paraffinic Distillate	64742-54-7	0.1 - 1	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

Note to physicians	Treat symptomatically.	
Indication of any immediate medical attention and special treatment needed		
Symptoms	No information available.	
Most important symptoms and effects, both acute and delayed		
Self-protection of the first aider	Use personal protective equipment as required.	
Ingestion	Rinse mouth. Drink plenty of water. If symptoms persist, call a physician. Do NOT induce vomiting.	
Inhalation	Remove to fresh air. Call a physician. If breathing is irregular or stopped, administer artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation.	
Skin Contact	Consult a physician if necessary. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.	
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.	
General advice	If symptoms persist, call a physician. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing.	

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

No information available.

Explosion data Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

	6. ACCIDENTAL RELEASE MEASURES		
Personal precautions, protective equipment and emergency procedures			
Personal precautions	Ensure adequate ventilation, especially in confined areas.		
Environmental precautions			
Environmental precautions	Prevent entry into waterways, sewers, basements or confined areas. Do not flush into surface water or sanitary sewer system.		
Methods and material for contain	inment and cleaning up		
Methods for containment	Prevent further leakage or spillage if safe to do so.		
Methods for cleaning up	Cover liquid spill with sand, earth or other non-combustible absorbent material. Use personal protective equipment as required. Dam up. Take up mechanically, placing in appropriate containers for disposal. Clean contaminated surface thoroughly.		

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handlingAvoid contact with skin, eyes or clothing. Use personal protective equipment as required.
Wash contaminated clothing before reuse. Do not breathe dust/fume/gas/mist/vapors/spray.
Do not eat, drink or smoke when using this product.

Conditions for safe storage, including any incompatibilities

Storage Conditions	Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of children.
Incompatible materials	None known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Titanium dioxide	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust	IDLH: 5000 mg/m ³
13463-67-7		(vacated) TWA: 10 mg/m ³ total dust	
Kaolin	TWA: 2 mg/m ³ particulate matter	TWA: 15 mg/m ³ total dust	TWA: 10 mg/m ³ total dust
1332-58-7	containing no asbestos and <1%	TWA: 5 mg/m ³ respirable fraction	TWA: 5 mg/m ³ respirable dust
	crystalline silica, respirable fraction	(vacated) TWA: 10 mg/m ³ total dust	
		(vacated) TWA: 5 mg/m ³ respirable	
		fraction	
Barium metaborate monohydrate	STEL: 6 mg/m ³ inhalable fraction	TWA: 0.5 mg/m ³ Ba	TWA: 0.5 mg/m ³ except Barium
13701-59-2	TWA: 0.5 mg/m ³ Ba TWA: 2 mg/m ³	(vacated) TWA: 0.5 mg/m ³ Ba	sulfate Ba
	inhalable fraction		

Ethylene Glycol 107-21-1	Ceiling: 100 mg/m ³ aerosol only	(vacated) Ceiling: 50 ppm (vacated) Ceiling: 125 mg/m ³	-
Zinc oxide, as Zn (fume)	STEL: 10 mg/m ³ respirable fraction	Ũ	IDLH: 500 mg/m ³
1314-13-2	TWA: 2 mg/m ³ respirable fraction	TWA: 15 mg/m ³ total dust	Ceiling: 15 mg/m ³ dust
		TWA: 5 mg/m ³ respirable fraction	TWA: 5 mg/m ³ dust and fume
		(vacated) TWA: 5 mg/m ³ fume	STEL: 10 mg/m ³ fume
		(vacated) TWA: 10 mg/m ³ total dust	-
		(vacated) TWA: 5 mg/m ³ respirable	
		fraction	
		(vacated) STEL: 10 mg/m ³ fume	

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls	Showers
	Eyewash stations
	Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection	Tight sealing safety goggles.
Skin and body protection	No special technical protective measures are necessary.
Respiratory protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.
General Hygiene Considerations	Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Appearance Color	liquid No information available No information available	Odor Odor threshold	No information available No information available
Property pH Melting point/freezing point Boiling point / boiling range Flash point Evaporation rate Flammability (solid, gas) Flammability Limit in Air Upper flammability limit: Lower flammability limit: Vapor pressure Vapor density Specific Gravity Water solubility Solubility in other solvents Partition coefficient Autoignition temperature Decomposition temperature Kinematic viscosity Dynamic viscosity Explosive properties	ValuesNo information availableNo information available>= 100 °C / 212 °F> 94 °C / > 201 °FNo information availableNo information available	<u>Remarks • Method</u>	
Explosive properties	No information available		

Other InformationSoftening pointNo information availableMolecular weightNo information availableVOC Content (%)No information availableDensity11.16 lbs/galBulk densityNo information availablePercent solids by weight54.4%	
Molecular weightNo information availableVOC Content (%)No information availableDensity11.16 lbs/galBulk densityNo information available	
Percent volatile by weight2.5%Percent solids by volume39.3%Actual VOC (lbs/gal)0.3Actual VOC (grams/liter)32.8EPA VOC (lbs/gal)0.6EPA VOC (grams/liter)77.6EPA VOC (lb/gal solids)0.7	

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Extremes of temperature and direct sunlight.

Incompatible materials

None known based on information supplied.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	No data available
Inhalation	No data available.
Eye contact	No data available.
Skin Contact	No data available.
Ingestion	No data available.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
Barium metaborate monohydrate 13701-59-2	= 3800 mg/kg (Rat)= 530 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	-
Ethylene Glycol 107-21-1	= 4700 mg/kg (Rat)	= 10600 mg/kg (Rat)= 9530 µL/kg (Rabbit)	-
Zinc oxide, as Zn (fume) 1314-13-2	> 5000 mg/kg (Rat)	-	-
Heavy Paraffinic Distillate 64742-54-7	> 15 g/kg (Rat)	-	-

Information on toxicological effects

Symptoms

No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization	No information available.			
Germ cell mutagenicity	No information available.			
Carcinogenicity	No information	on available.		
Chemical Name	ACGIH	IARC	NTP	OSHA
Titanium dioxide 13463-67-7	-	Group 2B	-	Х
Heavy Paraffinic Distillate 64742-54-7	A2	Group 1	-	X
Group 1 - Carcinogenic to Group 2B - Possibly Caro Group 3 - Not classifiable OSHA (Occupational Sa X - Present	cinogenic to Humans a as a human carcinogen afety and Health Administra	tion of the US Department of	f Labor)	
Reproductive toxicity	No information available.			
STOT - single exposure	No information available.			
STOT - repeated exposu	ure No information available.			
Target Organ Effects	s Central nervous system, Eyes, lungs, Respiratory system, Skin.			
Aspiration hazard	No information available.			
Numerical measures of t	oxicity - Product Inform	ation		

The following values are calculated based on chapter 3.1 of the GHS document mg/kg mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

31.56% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Ethylene Glycol	6500 - 13000: 96 h	41000: 96 h Oncorhynchus mykiss	46300: 48 h Daphnia magna mg/L
107-21-1	Pseudokirchneriella subcapitata	mg/L LC50 14 - 18: 96 h	EC50
	mg/L EC50	Oncorhynchus mykiss mL/L LC50	
		static 27540: 96 h Lepomis	
		macrochirus mg/L LC50 static	
		40761: 96 h Oncorhynchus mykiss	
		mg/L LC50 static 40000 - 60000: 96	
		h Pimephales promelas mg/L LC50	
		static 16000: 96 h Poecilia reticulata	
		mg/L LC50 static	
Heavy Paraffinic Distillate	-	5000: 96 h Oncorhynchus mykiss	1000: 48 h Daphnia magna mg/L
64742-54-7		mg/L LC50	ÉC50

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical Name	Partition coefficient
Ethylene Glycol	-1.93
107-21-1	

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastesDisposal should be in accordance with applicable regional, national and local laws and
regulations.Contaminated packagingDo not reuse container.

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
Barium metaborate monohydrate 13701-59-2	Тохіс
Zinc oxide, as Zn (fume) 1314-13-2	Тохіс

14. TRANSPORT INFORMATION

DOT

Not regulated

15. REGULATORY INFORMATION		
International Inventories		
TSCA	Complies	
DSL/NDSL	Complies *	
EINECS/ELINCS	Does not comply *	
ENCS	Does not comply *	
IECSC	Complies *	
KECL	Complies *	
PICCS	Complies *	
AICS	Complies *	

* This product contains an unknown chemical, therefore, this product's compliance to the inventory list is NOT DETERMINED

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %	
Barium metaborate monohydrate - 13701-59-2	1.0	

Ethylene Glycol - 107-21-1	1.0

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Zinc oxide, as Zn (fume) 1314-13-2	-	Х	-	-

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Ethylene Glycol	5000 lb	-	RQ 5000 lb final RQ
107-21-1			RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Titanium dioxide - 13463-67-7	Carcinogen
Crystalline Silica - 14808-60-7	Carcinogen
Lead Oxide - 1317-36-8	Carcinogen
	Developmental

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Titanium dioxide 13463-67-7	Х	X	Х
Kaolin 1332-58-7	Х	Х	Х
Barium metaborate monohydrate 13701-59-2	Х	-	Х
Ethylene Glycol 107-21-1	Х	Х	Х
Magnesium nitrate 10377-60-3	Х	Х	Х
Lead Oxide 1317-36-8	Х	Х	Х

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

Hazardous air pollutants (HAPS) content

LIST OF HAZARDOUS AIR POLLUTANTS SUBJECT TO THE PROVISIONS OF THE CLEAN AIR ACT, TITLE I SECTION 112 'National Emission Standards for Hazardous Air Pollutants':

Chemical Name	Weight % of HAPS in Product	Pounds HAPS / Gal Product
Ethylene Glycol 107-21-1	2.06%	0.23

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA_	Health hazards 2	Flammability 1	Instability 0	Physical and Chemical Properties -
HMIS	Health hazards 2 *	Flammability 1	Physical hazards 0	Personal protection X
Chronic Hazard Star Legend *= Chronic		ic Health Hazard		

Revision Date

12-May-2015

Revision Note No information available Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Shipping information may vary based upon container size and shipping destination. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage, or release to the environment. The manufacturer assumes no responsibility for injury to the recipient or third persons, or for any damages to any property resulting from misuse of the product.

End of Safety Data Sheet