

SAFETY DATA SHEET

Revision Date 12-May-2015 Version 2

1. IDENTIFICATION

Product identifier

Product Name Ext. Acrylic Latex Primer White

Other means of identification

Product Code 92224

SKU(s) 92221, 92224, 92225

Recommended use of the chemical and restrictions on use
Recommended Use
Uses advised against
No information available

Details of the supplier of the safety data sheet

Manufacturer Address Van Sickle Paint Mfg. Co.

PO Box 82222 Lincoln, NE 68501

Phone: 402-476-6558 Fax: 402-476-6749

Emergency telephone number

Emergency Telephone Chemtrec 1-800-424-9300

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity Category 1A

Emergency Overview

Danger

Hazard statements

May cause cancer



Appearance No information available

Physical state liquid

Odor No information available

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood Use personal protective equipment as required

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

Revision Date 12-May-2015

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other Information

Unknown acute toxicity 3.3% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%	Trade Secret
Titanium dioxide	13463-67-7	10 - 30	*
Barium metaborate monohydrate	13701-59-2	1 - 5	*
Kaolin	1332-58-7	1 - 5	*
Ethylene Glycol	107-21-1	1 - 5	*
Texanol	25265-77-4	1 - 5	*
Crystalline Silica	14808-60-7	0.1 - 1	*
Heavy Paraffinic Distillate	64742-54-7	0.1 - 1	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice If symptoms persist, call a physician. Do not breathe dust/fume/gas/mist/vapors/spray. Do

not get in eyes, on skin, or on clothing.

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms

persist, call a physician.

Skin Contact Consult a physician if necessary. Wash off immediately with soap and plenty of water while

removing all contaminated clothes and shoes.

Inhalation Remove to fresh air. Call a physician. If breathing is irregular or stopped, administer

artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth

resuscitation.

Ingestion Rinse mouth. Drink plenty of water. If symptoms persist, call a physician. Do NOT induce

vomiting.

Self-protection of the first aiderUse personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Indication of any immediate medical attention and special treatment needed

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

No information available.

Explosion data

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas.

Environmental precautions

Environmental precautions Prevent entry into waterways, sewers, basements or confined areas. Do not flush into

surface water or sanitary sewer system.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Cover liquid spill with sand, earth or other non-combustible absorbent material. Use

personal protective equipment as required. Dam up. Take up mechanically, placing in

appropriate containers for disposal. Clean contaminated surface thoroughly.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Avoid contact with skin, eyes or clothing. Use personal protective equipment as required.

Wash contaminated clothing before reuse. Do not breathe dust/fume/gas/mist/vapors/spray.

Do not eat, drink or smoke when using this product.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed in a dry and well-ventilated place. Keep out of the reach of

children.

Incompatible materials None known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Titanium dioxide	TWA: 10 mg/m ³	TWA: 15 mg/m³ total dust	IDLH: 5000 mg/m ³
13463-67-7		(vacated) TWA: 10 mg/m ³ total dust	
Barium metaborate monohydrate	STEL: 6 mg/m³ inhalable fraction	TWA: 0.5 mg/m³ Ba	TWA: 0.5 mg/m ³ except Barium
13701-59-2	TWA: 0.5 mg/m ³ Ba TWA: 2 mg/m ³	(vacated) TWA: 0.5 mg/m³ Ba	sulfate Ba
	inhalable fraction		
Kaolin	TWA: 2 mg/m³ particulate matter	TWA: 15 mg/m³ total dust	TWA: 10 mg/m ³ total dust
1332-58-7	containing no asbestos and <1%	TWA: 5 mg/m³ respirable fraction	TWA: 5 mg/m³ respirable dust
	crystalline silica, respirable fraction	(vacated) TWA: 10 mg/m³ total dust	
		(vacated) TWA: 5 mg/m³ respirable	
		fraction	

Ethylene Glycol 107-21-1	Ceiling: 100 mg/m³ aerosol only	(vacated) Ceiling: 50 ppm (vacated) Ceiling: 125 mg/m ³	-
Crystalline Silica 14808-60-7	TWA: 0.025 mg/m³ respirable fraction	(vacated) TWA: 0.1 mg/m³ respirable dust : (30)/(%SiO2 + 2) mg/m³ TWA total dust : (250)/(%SiO2 + 5) mppcf TWA respirable fraction : (10)/(%SiO2 + 2) mg/m³ TWA respirable fraction	IDLH: 50 mg/m³ respirable dust TWA: 0.05 mg/m³ respirable dust

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Skin and body protection No special technical protective measures are necessary.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state liquid

AppearanceNo information availableOdorNo information availableColorNo information availableOdor thresholdNo information available

Property Values Remarks • Method

pH 9.0-9.5

Melting point/freezing pointNo information availableBoiling point / boiling range>= 100 °C / 212 °FFlash point> 94 °C / > 201 °FEvaporation rateNo information availableFlammability (solid, gas)No information available

Flammability Limit in Air

Upper flammability limit:
Lower flammability limit:
Vapor pressure
Vapor density

No information available
No information available
No information available

Specific Gravity 1.27

Water solubility
Solubility in other solvents
Partition coefficient
Autoignition temperature
Decomposition temperature
Kinematic viscosity
No information available
No information available
No information available
No information available

Kinematic viscosity

Dynamic viscosity

Explosive properties

No information available
No information available
No information available

No information available

Other Information

Oxidizing properties

Softening pointNo information availableMolecular weightNo information availableVOC Content (%)No information available

Density 10.57 lbs/gal

Bulk density

No information available

Percent solids by weight 45.5% Percent volatile by weight 3.7% Percent solids by volume 31.2% Actual VOC (lbs/gal) 0.4 Actual VOC (grams/liter) 47.3 EPA VOC (lbs/gal) 1.1 EPA VOC (grams/liter) 132.4 EPA VOC (lb/gal solids) 1.3

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Extremes of temperature and direct sunlight.

Incompatible materials

None known based on information supplied.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information No data available

Inhalation No data available.

Eye contact No data available.

Skin Contact No data available.

Ingestion No data available.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
Barium metaborate monohydrate 13701-59-2	= 3800 mg/kg (Rat) = 530 mg/kg (Rat)	> 2000 mg/kg(Rabbit)	-
Ethylene Glycol 107-21-1	= 4700 mg/kg (Rat)	= 10600 mg/kg (Rat)= 9530 μL/kg (Rabbit)	-
Texanol 25265-77-4	= 3200 mg/kg (Rat)	> 15200 mg/kg (Rat)	-
Crystalline Silica 14808-60-7	= 500 mg/kg (Rat)	-	-

92224 Ext. Acrylic Latex Primer White

Heavy Paraffinic Distillate	> 15 g/kg (Rat)	-	-
64742-54-7			

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

SensitizationNo information available.Germ cell mutagenicityNo information available.CarcinogenicityNo information available.

Chemical Name	ACGIH	IARC	NTP	OSHA
Titanium dioxide 13463-67-7	-	Group 2B	-	Х
Crystalline Silica 14808-60-7	A2	Group 1	Known	Х
Heavy Paraffinic Distillate 64742-54-7	A2	Group 1	-	Х

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans Group 3 - Not classifiable as a human carcinogen

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity
STOT - single exposure
STOT - repeated exposure
No information available.
No information available.

Target Organ Effects Central nervous system, Eyes, lungs, Respiratory system, Skin.

Aspiration hazard No information available.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document mg/kg mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

24.68% of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Ethylene Glycol	6500 - 13000: 96 h	41000: 96 h Oncorhynchus mykiss	46300: 48 h Daphnia magna mg/L
107-21-1	Pseudokirchneriella subcapitata	mg/L LC50 14 - 18: 96 h	EC50
	mg/L EC50	Oncorhynchus mykiss mL/L LC50	
		static 27540: 96 h Lepomis	
		macrochirus mg/L LC50 static	
		40761: 96 h Oncorhynchus mykiss	
		mg/L LC50 static 40000 - 60000: 96	
		h Pimephales promelas mg/L LC50	
		static 16000: 96 h Poecilia reticulata	
		mg/L LC50 static	
Texanol	18.4: 72 h Pseudokirchneriella	30: 96 h Pimephales promelas mg/L	95: 96 h Daphnia magna mg/L LC50
25265-77-4	subcapitata mg/L EC50	LC50	
Heavy Paraffinic Distillate	-	5000: 96 h Oncorhynchus mykiss	1000: 48 h Daphnia magna mg/L
64742-54-7		mg/L LC50	EC50

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical Name	Partition coefficient
Ethylene Glycol 107-21-1	-1.93
Texanol 25265-77-4	3.47

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal should be in accordance with applicable regional, national and local laws and Disposal of wastes

regulations.

Contaminated packaging Do not reuse container.

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
Barium metaborate monohydrate	Toxic
13701-59-2	

14. TRANSPORT INFORMATION

DOT Not regulated

15. REGULATORY INFORMATION

International Inventories

Complies **DSL/NDSL** Complies * **EINECS/ELINCS** Does not comply * **ENCS** Does not comply * **IECSC** Complies * Complies * **KECL**

PICCS Does not comply * Complies * AICS

TSCA

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

^{*} This product contains an unknown chemical, therefore, this product's compliance to the inventory list is NOT DETERMINED

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %	
Barium metaborate monohydrate - 13701-59-2	1.0	
Ethylene Glycol - 107-21-1	1.0	

SARA 311/312 Hazard Categories

Yes
No
No
No
No

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Ethylene Glycol	5000 lb	-	RQ 5000 lb final RQ
107-21-1			RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65	
Titanium dioxide - 13463-67-7	Carcinogen	
Crystalline Silica - 14808-60-7	Carcinogen	

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Titanium dioxide 13463-67-7	X	X	X
Barium metaborate monohydrate 13701-59-2	X	-	X
Kaolin 1332-58-7	X	X	X
Ethylene Glycol 107-21-1	X	X	X
Crystalline Silica 14808-60-7	X	X	X
Magnesium nitrate 10377-60-3	Х	X	Х

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

Hazardous air pollutants (HAPS) content

LIST OF HAZARDOUS AIR POLLUTANTS SUBJECT TO THE PROVISIONS OF THE CLEAN AIR ACT, TITLE I SECTION 112 'National Emission Standards for Hazardous Air Pollutants':

Chemical Name	Weight % of HAPS in Product	Pounds HAPS / Gal Product
Ethylene Glycol 107-21-1	2.22%	0.23

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

<u>NFPA</u>	Health hazards 2	Flammability 1	Instability 0	Physical and Chemical
				Properties -
HMIS	Health hazards 2 *	Flammability 1	Physical hazards 0	Personal protection X

tex Primer White Revision Date 12-May-2015

Chronic Hazard Star Legend *= Chronic Health Hazard

Revision Date Revision Note 12-May-2015

No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Shipping information may vary based upon container size and shipping destination. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage, or release to the environment. The manufacturer assumes no responsibility for injury to the recipient or third persons, or for any damages to any property resulting from misuse of the product.

End of Safety Data Sheet