LB-45

Boiled Linseed Oil

Product Data Sheet

PRODUCT DESCRIPTION:

Van Sickle® LB-45 Boiled Linseed Oil is a 100% pure linseed oil, treated through a special process to strengthen its modular structure for all uses.

TYPICAL USES:

Van Sickle® LB-45 can be mixed with oil base paints or used by itself to give a tough, elastic film that resists weathering. As an additive to oil base paints, LB-45 improves flow and allows easier brushing of paint.

BASES & COLORS:

LB-45 Boiled Linseed Oil: Yellow/Brown

PHYSICAL PROPERTIES:

PRODUCT NUMBER:	LB-45
GENERAL TYPE:	Boiled Linseed Oil
COLOR:	Yellow/ Brown
SOLIDS BY WEIGHT:	99.90%
SOLIDS BY VOLUME:	99.98%
VISCOSITY @ 78°F:	N/A
THEORETICAL COVERAGE @ 1mil DFT:	1602.23 sq ft
WEIGHT PER GALLON:	7.77 lbs.
FLASH POINT:	450°F
VOC:	0.01 g/L

SURFACE PREPARATION:

If using LB-45 in conjunction with a paint product, please refer to that products label for directions on proper surface preparation.

APPLICATION:

As an additive: Follow the instructions given on the paint product label. Do not use more than the recommended amount. Using by itself: On furniture, hand tools, guns, golf clubs and similar surfaces that will be handled, oil should be rubbed in and excess wiped clean. Properly applied, LB-45 will be neither gummy nor odorous, and dries in 12 to 18 hours.

Dry Times:

As an Additive: Dry times will depend on the product LB-45 is being added to.

By itself: When used properly, LB-45 should be dry within 12 to 18 hours.

Van Sickle Paint
PO Box 82222 Lincoln Ne, 68501
1-800-677-2468

Product Data Sheet

CAUTIONS:

Oil soaked rags or other oily waste may be subject to spontaneous combustion. To avoid possible fire hazard, promptly discard in water filled container, or burn all rags in a safe burning container, following all state and local guidelines. Avoid contact with eyes, skin and clothing. In case of eye contact, flush eyes with water for 15 minutes and call poison control center, or seek medical attention immediately. Wash thoroughly after handling. Keep out of reach of children. If ingested, do not induce vomiting; seek medical treatment immediately.

For additional Product Information or Safety Data Sheets, please call 800-677-2468, 8:00-5:00 CST Mon.-Fri.

Limited Warranty:

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since Van Sickle®Paint does not control the application of its products, or the condition of the surfaces to which they are applied, Van Sickle®Paint's liability will under no circumstances exceed replacement of the product.

Van Sickle Paint
PO Box 82222 Lincoln Ne, 68501
1-800-677-2468