



Super Thinner

High Grade Mineral Spirits; Paint Thinner

Product Data Sheet

PRODUCT DESCRIPTION:

Van Sickle® ST-30 Super Thinner is an all-purpose reducer or thinner intended to be used with oil base paint, varnishes and enamels. It has a mild odor and contributes to better flow and brushing properties.

TYPICAL USES:

Van Sickle® ST-30 can be used wherever turpentine, mineral spirits, or painter's naphtha is recommended. Ideal for cleaning brushes, rollers, tools, and hands after painting.

BASES & COLORS:

ST-30 Super Paint Thinner; Clear

PHYSICAL PROPERTIES:

PRODUCT NUMBER:	ST-30
GENERAL TYPE:	Paint Thinner; Mineral Spirits
COLOR:	Clear
SOLIDS BY WEIGHT:	0.00%
SOLIDS BY VOLUME:	0.00%
VISCOSITY @ 78°F:	N/A
WEIGHT PER GALLON:	6.5 lbs.
FLASH POINT:	102°F
VOC:	779.19 G/L

SURFACE PREPARATION:

This product is intended to be used in conjunction with the recommended Van Sickle® Paint products as a reduction solvent; please follow directions for the product to which you adding ST-30 to.

APPLICATION:

Add up to one pint of Van Sickle® ST-30 to one gallon of Van Sickle® Tractor & Equipment Enamel or Van Sickle Multi-Purpose Enamel. Stir thoroughly. When using this Reducer with Clear Hardener, incorporate the hardener first as directed on the Hardener label. ST-30 Thinner may also be used with Van Sickle® Tractor & Equipment Enamel Primer.



Super Thinner

High Grade Mineral Spirits; Paint Thinner

Product Data Sheet

CAUTIONS:

Combustible liquid and vapor. Vapor harmful; may affect the brain or nervous system causing dizziness, headache or nausea. Causes nose, throat, lung and skin irritation. Use only with adequate ventilation. Avoid contact with eyes, skin and clothing. In case of eye contact, flush eyes with water for 15 minutes and call poison control center, or seek medical attention immediately. Wash thoroughly after handling. Keep out of reach of children. If ingested, do not induce vomiting; seek medical treatment immediately.

For additional Product Information or Safety Data Sheets, please call 800-677-2468, 8:00-5:00 CST Mon.-Fri.

Limited Warranty:

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since Van Sickle®Paint does not control the application of its products, or the condition of the surfaces to which they are applied, Van Sickle®Paint's liability will under no circumstances exceed replacement of the product.