

Interior Polyurethane

Satin, Clear

Product Data Sheet**PRODUCT DESCRIPTION:**

Van Sickle® Polyurethane Clear Finish is the ultimate in premium quality clear finishes. It features fast dry, superior mar and scuff resistance, and will withstand extremes of wear and water exposure. Van Sickle Polyurethane Clear Finish is extremely tough and flexible, and is ideal for interior wood. It is especially suited for properly prepared interior wood floors, porches, industrial applications, table tops, furniture, bar tops, cabinets, doors church pews, and concrete floors.

TYPICAL USES:

Use on wood floors, garage, or basement floors, and on floors in large warehouses, industrial, and commercial buildings.

BASES & COLORS:

006 Clear Satin

PHYSICAL PROPERTIES:

PRODUCT NUMBER:	006
GENERAL TYPE:	Polyurethane Varnish Satin
COLOR:	Clear
SOLIDS BY WEIGHT:	49.5%
SOLIDS BY VOLUME:	42.4%
THEORETICAL COVERAGE @ 1 MIL DFT:	680 Square Feet per Gallon
RECOMMENDED DFT:	Not Recommended
VISCOSITY @ 78°F:	20-25 Seconds
WEIGHT PER GALLON:	7.2 lbs.
FLASH POINT:	102°F
VOC:	450 G/L

SURFACE PREPARATION:

For best results, all surfaces must be clean and dry. All floors must be carefully cleaned before sealer application, and must be free from wax, grease, oil, dirt, and curing compounds. Unfinished wood: sand smooth and wipe clean. Fill all open grain wood with paste wood filler. Stain surfaces if desired, and allow to dry according to stain manufacturers recommendations. Apply sealer coat of Polyurethane Clear Finish, allow to dry, sand lightly and wipe clean. Finish with one or two coats as needed, sanding lightly between coats. Unpainted concrete should be etched with a 5% phosphoric acid mixture and rinsed thoroughly. New concrete must cure for a minimum of at least 60 days before etching.

APPLICATION:

Apply by brush, roller, or spray Use as is from the container; do not thin. For brushing, use a natural bristle brush and apply as is from the container. Flow on and smooth out, avoid excessive brushing. For roller application, use a cover with a short nap cover suited for varnish, to avoid bubbles. Before and during use, please stir contents to avoid settling of the resins.

ENVIRONMENTAL VARIABLES:

Apply only when surface, air, and coating temperatures are between 50° and 90°F. Conditions that are cool, humid, or wet, over application of the product, or multiple coats applied too quickly can all result in extended dry time and interfere with proper film formation.

Dry-Times:

Under ideal drying times product will be dry to touch in six hours, and may walked upon after 24 hours.

Interior Polyurethane

Satin, Clear

Product Data Sheet

CLEAN-UP:

Clean all tools and equipment immediately with high grade mineral spirits before product dries.

CAUTIONS:

Do not take internally,

Use with adequate ventilation,

KEEP OUT OF REACH OF CHILDREN

*WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the national Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

For additional Product Information or Safety Data Sheets, please call 800-677-2468, 8:00-5:00 CST

Limited Warranty:

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since Van Sickle Paint does not control the application of its products, or the condition of the surfaces to which they are applied, Van Sickle Paint's liability will under no circumstances exceed replacement of the product.