

Enamel Undercoat

Interior Oil, Flat White

Product Data Sheet**PRODUCT DESCRIPTION:**

Van Sickle® Interior Enamel Undercoat is custom built for exceptional hiding, stain control and easy working qualities. Van Sickle Interior Enamel Undercoat provides a nonporous surface that prevents the “striking in” of succeeding coats of enamel and forms an ideal foundation for any finish which will not check or chip. Van Sickle Interior Enamel Undercoat meets or exceeds the quality or most equally priced undercoats on the market. USE ON interior bare wood surfaces and many other previously painted surfaces.

TYPICAL USES:

Interior bare wood surfaces and many other previously painted surfaces.

BASES & COLORS:

080 Flat White, Oil

PHYSICAL PROPERTIES:

PRODUCT NUMBER:	080
GENERAL TYPE:	Interior Oil Enamel Undercoat
COLOR:	White
SOLIDS BY WEIGHT:	75.9%
SOLIDS BY VOLUME:	56.1%
THEORETICAL COVERAGE @ 1 MIL DFT:	900 Square Feet Per Gallon
RECOMMENDED DFT:	1.5 Mils
VISCOSITY @ 78°F:	72-76 KU
WEIGHT PER GALLON:	11.8- 12.0 lbs.
FLASH POINT:	102°F
VOC:	177 G/L

SURFACE PREPARATION:

For best results, all surfaces must be clean and dry and free of wax, oil grease, dirt, mildew and any foreign matter or contaminants. New bare wood surfaces should be coated with Enamel Undercoat, allow to dry and carefully sand. Enamel Undercoat may be used on interior drywall surfaces where humid conditions may exist (bathrooms, kitchens, etc.). If used on drywall, a light sanding will be necessary to remove rough finish created by drywall paper.

APPLICATION:

Apply by natural bristle brush, roller or spray. DO NOT THIN; use as is from the container. DO NOT APPLY on damp surfaces. Do not use this product near or around open flames and extinguish all pilot lights.

ENVIRONMENTAL VARIABLES:

Apply only when surface, air, and coating temperatures are between 50° and 90°F. Conditions that are cool, humid, or wet, over application of the product, or multiple coats applied too quickly can all result in extended dry time and interfere with proper film formation.

Dry-Times:

Under ideal drying times, product will be dry to touch in 24 hours, and may be recoated after 48 hours under ideal drying conditions.

CLEAN-UP:

Clean all tools and equipment immediately with high grade mineral spirits before product dries.

Enamel Undercoat

Interior Oil, Flat White

Product Data Sheet

CAUTIONS:

Do not take internally,

Use with adequate ventilation,

KEEP OUT OF REACH OF CHILDREN

*WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the national Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

For additional Product Information or Safety Data Sheets, please call 800-677-2468, 8:00-5:00 CST Mon.-Fri.

Limited Warranty:

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since Van Sickle Paint does not control the application of its products, or the condition of the surfaces to which they are applied, Van Sickle Paint's liability will under no circumstances exceed replacement of the product.