Earth Brown

Alkyd, Oil Based Enamel



Product Data Sheet

PRODUCT DESCRIPTION:

Van Sickle Camo Paint is made for the serious sportsman wanting to successfully break-up outlines and shapes by blending an object into most exterior backgrounds, bringing you closer to nature.

TYPICAL USES:

Camo Paint can be used to camouflage vehicles, boats, trailers, duck blinds, tree stands, ladders, ladder stands, guns and bows – almost any surface where a camouflage coating is needed. Camo Paint can be used for natural crafts as a base coat under decoys, tole painting and a variety of applications where natural and flat earth-tone finishes are desired.

BASES & COLORS:

102 Earth Brown

PHYSICAL PROPERTIES:

PRODUCT NUMBER: 102

GENERAL TYPE: Alkyd Oil Based

COLOR: Earth Brown

SOLIDS BY WEIGHT: 60.07%

SOLIDS BY VOLUME: 39.73%

THEORETICAL COVERAGE @ 1 MIL DFT:

637.34Sq.Ft/Gal

RECOMMENDED DFT: 2 - 2.5 mils

VISCOSITY @ 78°F: 89 – 90 KU

WEIGHT PER GALLON: 9.73 lbs.

FLASH POINT: 102° F

VOC: 466.18 G/L

SURFACE PREPARATION:

For best results, all surfaces must be clean, dry, and free from wax, oil, grease, dirt mildew, loose rust, and any other contaminants. Dulling a glossy surface helps adhesion and improves the life of the Camo finish.

APPLICATION:

Apply brush, roller, or spray.

ENVIRONMENTAL VARIABLES:

Apply only when surface and air temperatures are between 50° and 90°F. Avoid painting on hot days, in direct sunlight or late in the day when dew is likely to form. Cool, wet, humid, or overapplied coatings can greatly increase through cure and interfere with proper film formation. Do not apply at temperatures below 40°F.

Dry-Times:

Under ideal drying times product will be dry to touch in one hour and may be recoated in 6 hours.

CLEAN-UP:

Clean all tools and equipment immediately with mineral spirits.

Earth Brown

Alkyd, Oil Based Enamel



Product Data Sheet

CAUTIONS:

For exterior use only,

Do not take internally,

Use with adequate ventilation,

KEEP OUT OF REACH OF CHILDREN

*WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the national Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

For additional Product Information or Safety Data Sheets, please call 800-677-2468, 8:00-5:00 CST Mon.-Fri.

Limited Warranty:

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since Van Sickle Paint does not control the application of its products, or the condition of the surfaces to which they are applied, Van Sickle Paint's liability will under no circumstances exceed replacement of the product.