



White Traffic Paint
Interior/Exterior Oil

Product Data Sheet

PRODUCT DESCRIPTION:

Van Sickle® Oil based Traffic Paint is our custom designed coating, made with top grade pigments and alkyd resins.

TYPICAL USES:

Van Sickle® Oil based Traffic Paint is formulated and recommended for marking and striping streets, highways, or other traffic surfaces, including driveways, parking lots, sidewalks, curbs, airport runways, berms, factory aisles, factory safety markings, and tennis courts.

BASES & COLORS:

110 White, Oil Base

PHYSICAL PROPERTIES:

PRODUCT NUMBER:	110
GENERAL TYPE:	Traffic Paint; Oil
COLOR:	White
SOLIDS BY WEIGHT:	71.00%
SOLIDS BY VOLUME:	48.00%
THEORETICAL COVERAGE @ 16 MIL DFT:	
	300 Sq.Ft/Gal
RECOMMENDED DFT:	7.7 mils
VISCOSITY @ 78°F:	70 – 80 KU
WEIGHT PER GALLON:	11.5 lbs.
FLASH POINT:	32° F
VOC:	450 G/L

SURFACE PREPARATION:

For best results, all surfaces must be clean, dry and free from wax, oil, grease, dirt mildew, loose rust and any other contaminants. Remove any loose, peeling or poorly bonded paint by wire brush or sandblasting. New concrete must cure at least 60 days before acid etching, and unpainted new concrete must be etched with a 5% phosphoric acid solution.

APPLICATION:

Apply by roller, airless or air spray. DO NOT THIN; apply as is from the container. Adequate mixing may be necessary to ensure proper coverage, durability, color uniformity, and application properties.

ENVIRONMENTAL VARIABLES:

Apply only when surface and air temperatures are between 40° and 100°F. Avoid painting late in the day when dew is likely to form, or when rain is forecasted. Cool, wet, humid or over-applied coatings can greatly increase through cure and interfere with proper film formation. Do not apply at temperatures below 40°F. Over application of the product, or multiple coats applied too quickly can all result in extended dry time and interfere with proper film formation.

Dry-Times:

Under ideal drying times product will be dry to touch in 1 to 2 hours, and may be recoated after 4 hours. When applying more than one coat, always allow the previous coat to dry thoroughly before application of subsequent coats.

CLEAN-UP:

Clean all tools and equipment with VM&P Naptha before paint dries.



White Traffic Paint
Interior/Exterior Oil

Product Data Sheet

CAUTIONS:

For exterior use only,

Do not take internally,

Use with adequate ventilation,

KEEP OUT OF REACH OF CHILDREN

*WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the national Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

For additional Product Information or Safety Data Sheets, please call 800-677-2468, 8:00-5:00 CST Mon.-Fri.

Limited Warranty:

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since Van Sickle®Paint does not control the application of its products, or the condition of the surfaces to which they are applied, Van Sickle®Paint's liability will under no circumstances exceed replacement of the product.