

Product Data Sheet

PRODUCT DESCRIPTION:

Van Sickle® Exterior Latex Stain is our custom built formula for exterior wood surfaces. It has excellent color retention, durability and resistance to weathering. Van Sickle® Exterior Latex Stain meets or exceeds the quality of most equally priced concrete sealers on the market.

TYPICAL USES:

Van Sickle® Exterior Latex Stain is ideal for use on rough wood siding, wood picnic tables, patio furniture, wood fences and decks. Van Sickle® Exterior Latex Stain achieves protection of surface through penetration, not through mil buildup; therefore it is not recommended to build a film thickness with this product.

BASES & COLORS:

250 Exterior Latex Stain
Redwood

PHYSICAL PROPERTIES:

PRODUCT NUMBER:	250
GENERAL TYPE:	Exterior Latex Stain
COLOR:	Redwood
GLOSS:	N/A
SOLIDS BY WEIGHT:	22.9 %
SOLIDS BY VOLUME:	14.7%
THEORETICAL COVERAGE @ 1 MIL DFT:	236Sq.Ft/Gal
RECOMMENDED DFT: RECOMMENDED	FILM BUILD UP NOT RECOMMENDED
VISCOSITY @ 78°F:	65-75 KU
WEIGHT PER GALLON:	9.2-9.3lbs.
FLASH POINT:	NONE
VOC:	152 G/L

SURFACE PREPARATION:

Proper surface preparation is the most important variable in determining the service life of a coating. For best results, all surfaces must be clean, dry and free from wax, oil, grease, dirt, mildew, loose paint and any other contaminants.

APPLICATION:

Apply by brush, roller or spray. If thinning is needed, thin up to 10% with clean water. Apply evenly with nylon brush and brush out with the grain of the wood. Before and during use, stir product thoroughly from the bottom of the container with an upward motion, scraping the bottom of avoid pigment settling. If more concealment of the grain is desired, a second coat of Van Sickle® Exterior Latex Stain may be applied after 12 hours.

ENVIRONMENTAL VARIABLES:

Apply only when surface and air temperatures are between 50° and 90°F. Do not apply product on hot days in direct sunlight. Avoid painting late in the day when dew and condensation are likely to form, or when rain is threatening. Conditions that are cool, humid or wet, over application of the product, or multiple coats applied too quickly can all result in extended dry time.

Dry-Times:

Drying time for this product will be approximately 6 hours to touch, and may be recoated after 12 hours of ideal drying conditions.

CLEAN-UP:

Clean up all tools and equipment immediately with warm, soapy water. To avoid spontaneous combustion during temporary storage, soak soiled rags and waste immediately after use in a water-filled, closed metal container.



250

Exterior Latex Stain
Redwood



Product Data Sheet

CAUTIONS:

For exterior use only,
Do not take internally,
Use with adequate ventilation,
KEEP OUT OF REACH OF CHILDREN

*WARNING! If you scrape, sand, or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the national Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

For additional Product Information or Safety Data Sheets, please call 800-677-2468, 8:00-5:00 CST Mon.-Fri.

Limited Warranty

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since Van Sickle Paint does not control the application of its products, or the condition of the surfaces to which they are applied, Van Sickle Paint's liability will under no circumstances exceed replacement of the product.

