

Product Data Sheet

PRODUCT DESCRIPTION:

Van Sickle® Exterior Oil Stain is our quality stain custom built to beautify, preserve and repel water on exterior wood surfaces. It is formulated for superior performance with top quality pigments, linseed oil and water repellants and is designed to protect and enrich the natural beauty of the wood.

TYPICAL USES:

Van Sickle® Exterior Oil Stain is ideal for USE ON rough cut or smooth cut lumber, picnic tables, patio furniture, wood fences or decks. Van Sickle® Exterior Oil Stain will seal, stain and finish in one coat. It has excellent color retention, durability and resistance to weathering.

BASES & COLORS:

258 Exterior Oil Stain
Rich Redwood

PHYSICAL PROPERTIES:

PRODUCT NUMBER:	258
GENERAL TYPE:	Exterior Oil Stain
COLOR:	Rich Redwood
GLOSS:	N/A
SOLIDS BY WEIGHT:	38.2%
SOLIDS BY VOLUME:	29.4%
THEORETICAL COVERAGE @ 1 MIL DFT:	547Sq.Ft/Gal
RECOMMENDED DFT: RECOMMENDED	FILM BUILD UP NOT RECOMMENDED
VISCOSITY @ 78°F:	20-25 sec.
WEIGHT PER GALLON:	7.4-7.5lbs.
FLASH POINT:	102
VOC:	550 G/L

SURFACE PREPARATION:

Proper surface preparation is the most important variable in determining the service life of a coating. For best results, all surfaces must be clean, dry and free from wax, oil, grease, dirt, mildew, loose paint and any other contaminants.

APPLICATION:

Apply by natural bristle brush, roller or spray. DO NOT THIN; use as is from the container. Do not add latex or oil-based products to the stain. If more concealment of the grain is desired, a second coat of Oil Stain may be applied after 48 hours. A film buildup of this product is not desired; protection and natural beauty are achieved by penetration of the linseed oils into the wood surface. Before and during use, stir product thoroughly from the bottom of the container with an upward motion, scraping the bottom of avoid pigment settling.

ENVIRONMENTAL VARIABLES:

Apply only when surface and air temperatures are between 50° and 90°F. Do not apply product on hot days in direct sunlight. Avoid painting late in the day when dew and condensation are likely to form, or when rain is threatening. Conditions that are cool, humid or wet, over application of the product, or multiple coats applied too quickly can all result in extended dry time.

Dry-Times:

Drying time for this product will be approximately 24 hours to touch, and may be recoated after 48 hours of ideal drying conditions.

CLEAN-UP:

Clean up all tools and equipment immediately with high grade mineral spirits before paint dries. To avoid spontaneous combustion during temporary storage, soak soiled rags and waste immediately after use in a water-filled, closed metal container.



258

Exterior Oil Stain
Rich Redwood



Product Data Sheet

CAUTIONS:

For exterior use only,
Do not take internally,
Use with adequate ventilation,
KEEP OUT OF REACH OF CHILDREN

*WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the national Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

For additional Product Information or Safety Data Sheets, please call 800-677-2468, 8:00-5:00 CST Mon.-Fri.

Limited Warranty

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since Van Sickle Paint does not control the application of its products, or the condition of the surfaces to which they are applied, Van Sickle Paint's liability will under no circumstances exceed replacement of the product.

