

Product Data Sheet

PRODUCT DESCRIPTION:

Van Sickle® Oil Based Barn Paint is our Super Premium quality exterior finish custom designed for use on farm and ranch buildings, other utility buildings and fences. It gives a uniform finish that will protect and beautify the surface for years. It is formulated for high hiding, excellent color retention and outstanding durability. Van Sickle® Barn Paints are premixed and exceed the quality of most equally priced barn paints on the market. It is formulated with top grade resin, linseed oil, and fade resistant pigments.

TYPICAL USES:

This formulation makes it ideal for painting properly prepared wood surfaces. **DO NOT** apply linseed oil based paints over metal or steel, these surfaces do not allow for linseed oil to dry properly.

BASES & COLORS:

540 Barn & Outbuilding Oil Semi-Gloss
Flaming Scarlet

PHYSICAL PROPERTIES:

PRODUCT NUMBER:	540	
GENERAL TYPE:	Linseed Based Exterior	Oil
COLOR:	Flaming Scarlet	
GLOSS:	85+ @ 60°	
SOLIDS BY WEIGHT:	88.5 %	
SOLIDS BY VOLUME:	61.0 %	
THEORETICAL COVERAGE @ 1 MIL DFT:	978 Sq.Ft/Gal	
RECOMMENDED DFT:	1.5 - 2.0 mils DFT	
VISCOSITY @ 78°F:	70 - 74 KU	
WEIGHT PER GALLON:	8.0 – 8.1 lbs.	
FLASH POINT:	102°F	
VOC:	305 G/L	

SURFACE PREPARATION:

Proper surface preparation is the most important variable in determining the service life of a coating. For best results, all surfaces must be clean, dry and free from wax, oil, grease, dirt, mildew, and any other contaminants. New surfaces must be properly cleaned and primed with the appropriate Van Sickle® Exterior Primer. Allow primer to dry thoroughly before application of the finish coat. For Previously Painted Surfaces, it is recommended that highly weathered areas be sanded. Bare spots where the old film has been removed down to the wood must be spot primed with an appropriate wood primer.

APPLICATION:

Apply by natural bristle brush, roller or spray. **Do Not Thin**; use as is from the container. Do not add oils or any other paints to this product. Before and during application, stir the paint thoroughly from the bottom of the can with an upward motion, scraping the bottom to avoid pigment settling.

ENVIRONMENTAL VARIABLES:

Apply only when surface and air temperatures are between 50° and 90°F. Avoid painting on hot days, in direct sunlight or late in the day when dew is likely to form. Cool, wet, humid or over-applied coatings can greatly decrease a thorough cure and interfere with proper film formation.

Dry-Times:

Drying time for this product will be 24 hours to touch, and may be recoated after 48 hours under ideal drying conditions.

CLEAN-UP:

Clean up all tools and equipment with Mineral Spirits before paint is allowed to dry. To avoid spontaneous combustion during storage, soak soiled rags and waste immediately after use in a water-filled closed metal container.



540

Barn & Outbuilding Oil Semi-Gloss
Flaming Scarlet



Product Data Sheet

CAUTIONS:

For exterior use only,
Do not take internally,
Use with adequate ventilation,
KEEP OUT OF REACH OF CHILDREN

*WARNING! If you scrape, sand, or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the national Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

For additional Product Information or Safety Data Sheets, please call 800-677-2468, 8:00-5:00 CST Mon.-Fri.

Limited Warranty

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since Van Sickle Paint does not control the application of its products, or the condition of the surfaces to which they are applied, Van Sickle Paint's liability will under no circumstances exceed replacement of the product.

