

Product Data Sheet

PRODUCT DESCRIPTION:

Sure-Block® is an interior-exterior alkyd stain blocking primer that is specifically designed to block stains on both interior and exterior surfaces. It is ideal for use on painted or unpainted wood, plaster, hardboard and drywall. It also seals burned or charred surfaces, old water stains, and seals back lipstick, crayon, ball-point ink stains, smoke, and grease. Sure-Block® is also suitable to be used as an exterior wood primer to seal water soluble tannin stains. This Van Sickle® stain blocking primer meets or exceeds the quality of most equally priced primers on the market.

TYPICAL USES:

Van Sickle® Sure-Block® Primer is designed for use on previously painted interior wood, plaster, and drywall surfaces in kitchens where grease and smoke stains are a problem; seals fire and smoke damage on walls, ceramic and plaster tile. Topcoat with any Van Sickle® interior or exterior latex finish, Tractor, Equipment and Industrial Enamel or oil base finishes.

BASES & COLORS:

622 Sure-Block® Primer

PHYSICAL PROPERTIES:

PRODUCT NUMBER:	622
GENERAL TYPE:	Oil Base Primer; Alkyd
COLOR:	White
GLOSS:	N/A @ 60°
SOLIDS BY WEIGHT:	63.60%
SOLIDS BY VOLUME:	41.00%
THEORETICAL COVERAGE @ 1 MIL DFT:	657Sq.Ft/Gal
RECOMMENDED DFT:	1.5 - 2mils DFT
VISCOSITY @ 78°F:	63 - 67 KU
WEIGHT PER GALLON:	10.45 lbs.
FLASH POINT:	102°F
VOC:	450 G/L

SURFACE PREPARATION:

Proper surface preparation is the most important variable in determining the service life of a coating. For best results, all surfaces must be clean, dry and free from wax, oil, grease, dirt, mildew, loose rust and any other contaminants. Wood Surfaces should be sanded smooth, with all nail holes and imperfections being corrected before application. Plaster Surfaces must cure for a minimum of 30 days at 72°F prior to application. Drywall Surfaces should be smooth and free of imperfections, allowing spackling compound to dry fully before application. Alkyd coatings are Not recommended for direct application to unprimed masonry surfaces or unprimed galvanized surfaces.

APPLICATION:

Apply by natural bristle brush, or spray. A good quality natural bristle brush will make application easier. Select a roller cover suited for the texture of the surface to be coated. Airless tip sizes of .013 to .015 are recommended. Intermix tinted containers to ensure color uniformity of all material. Apply product in full even coats and maintain a wet edge. Allow product to dry and then sand lightly before applying a topcoat. Do not thin. Before and during application, stir the paint thoroughly from the bottom of the can with an upward motion, scraping the bottom to avoid pigment settling.

ENVIRONMENTAL VARIABLES:

Apply only when surface and air temperatures are between 50° and 90°F. Avoid painting on hot days, in direct sunlight or late in the day when dew is likely to form. Cool, wet, humid or over-applied coatings can greatly decrease a thorough cure and interfere with proper film formation.

Dry-Times:

Drying time for this product will be approximately 10 minutes to touch, and may be recoated after 1½ hours under ideal drying conditions.

CLEAN-UP:

Clean up all tools and equipment with Mineral Spirits before paint is allowed to dry. To avoid spontaneous combustion during storage, soak soiled rags and waste immediately after use in a water-filled closed metal container.



622

Sure-Block®
Int. /Ext. Oil Primer



Product Data Sheet

CAUTIONS:

For exterior use only,
Do not take internally,
Use with adequate ventilation,
KEEP OUT OF REACH OF CHILDREN

***WARNING!** If you scrape, sand, or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the national Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

For additional Product Information or Safety Data Sheets, please call 800-677-2468, 8:00-5:00 CST Mon.-Fri.

Limited Warranty

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since Van Sickle Paint does not control the application of its products, or the condition of the surfaces to which they are applied, Van Sickle Paint's liability will under no circumstances exceed replacement of the product.

