

## Product Data Sheet

### **PRODUCT DESCRIPTION:**

Van Sickle® Interior Latex is designed for outstanding interior performance. Our custom-built formula provides easy application and reduced spatter. It is formulated for high hiding, fast drying, excellent color retention, and outstanding durability. This Van Sickle® Interior Latex Paint meets or exceeds the quality of most equally priced interior latex paints on the market.

### **TYPICAL USES:**

Van Sickle® Interior Latex is ideal for direct application to drywall or on all prepared interior walls.

### **BASES & COLORS:**

831 Interior Latex; Semi-gloss Finish  
White Candle

### **PHYSICAL PROPERTIES:**

PRODUCT NUMBER:	831
GENERAL TYPE:	Interior Latex; Semi-gloss
COLOR:	White Candle
GLOSS:	30-50 @ 60°
SOLIDS BY WEIGHT:	39.7%
SOLIDS BY VOLUME:	25.9%
THEORETICAL COVERAGE @ 1 MIL DFT:	416Sq.Ft/Gal
RECOMMENDED DFT:	2 – 2.5mils DFT
VISCOSITY @ 78°F:	95-100 KU
WEIGHT PER GALLON:	10.2 lbs.
FLASH POINT:	None
VOC:	96 G/L

### **SURFACE PREPARATION:**

Proper surface preparation is the most important variable in determining the service life of a coating. For best results, all surfaces must be clean, dry and free from wax, oil, grease, dirt, mildew, loose rust, and any other contaminants. Glossy surfaces must be dulled with sandpaper or de-glossing solution. Bare wood must be primed with enamel undercoat. Bare metal must be primed with Van Sickle® Equipment Enamel Primer. Previously painted surfaces must be properly prepared, then apply one or two coats of Van Sickle® Interior Latex Finish Coat.

### **APPLICATION:**

Apply by nylon or polyester brush, roller or spray. Apply as is from the container; if thinning is necessary for spray application, thin up to 10% with clean water. Do not add oil-based paints or thinners to this product. Before and during application, stir the paint thoroughly from the bottom of the can with an upward motion, scraping the bottom to avoid pigment settling.

### **ENVIRONMENTAL VARIABLES:**

Apply only when surface and air temperatures are between 50° and 90°F. Cool, wet, humid or over-applied coatings can greatly decrease a thorough cure and interfere with proper film formation. Always allow applied coat to dry before applying subsequent coats.

### **Dry-Times:**

Drying time for this product will be approximately 1 hour to touch, and may be recoated after 4 hours under ideal drying conditions.

### **CLEAN-UP:**

Clean up all tools and equipment with warm, soapy water before paint dries.



**831**

Interior Latex; Semi-gloss Finish  
White Candle



## Product Data Sheet

---

### **CAUTIONS:**

For interior use only,  
Do not take internally,  
Use with adequate ventilation,  
KEEP OUT OF REACH OF CHILDREN

\*WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the national Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

For additional Product Information or Safety Data Sheets, please call 800-677-2468, 8:00-5:00 CST Mon.-Fri.

### **Limited Warranty**

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since Van Sickle Paint does not control the application of its products, or the condition of the surfaces to which they are applied, Van Sickle Paint's liability will under no circumstances exceed replacement of the product.

