9090 1

Acrylic Enamel Reducer



Product Data Sheet

PRODUCT DESCRIPTION:

Dry-Times:

CLEAN-UP:

N/A

N/A

Van Sickle[®] Acrylic Enamel Reducer designed for use with Van Sickle[®] Tractor, Truck and Auto Acrylic Enamels.

TYPICAL USES:

Acrylic Enamel Reducer.

BASES & COLORS:

N/A

SURFACE PREPARATION:

N/A

APPLICATION:

Van Sickle[®] Acrylic Enamel Reducer may be used to thin Van Sickle[®]Acrylic Enamels or for clean-up. See finish coat in instruction for recommended ratios.

ENVIRONMENTAL VARIABLES:

Will vary depending on conditions at time of use.

PHYSICAL PROPERTIES:

PRODUCT NUMBER:	9090 1
GENERAL TYPE: Reducer	Acrylic Enamel
COLOR:	Clear
SOLIDS BY WEIGHT:	N/A
SOLIDS BY VOLUME:	N/A
THEORETICAL COVERAGE @	2 1 MIL DFT: N/A
RECOMMENDED DFT:	N/A
VISCOSITY @ 78°F:	N/A
WEIGHT PER GALLON:	6.93
FLASH POINT:	1°F
VOC:	835.28 G/L

Acrylic Enamel Reducer



Product Data Sheet

CAUTIONS:

For exterior use only,

Do not take internally,

Use with adequate ventilation,

KEEP OUT OF REACH OF CHILDREN

*WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE. **ESPECIALLY** IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear а NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the national Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

For additional Product Information or Safety Data Sheets, please call 800-677-2468, 8:00-5:00 CST Mon.-Fri.

Limited Warranty:

The technical data and suggestions for use contained in this document are true and correct to the best of our knowledge at the date of issuance. The statements of this document do not constitute a warranty, expressed or implied, as to the performance of these products. Since Van Sickle®Paint does not control the application of its products, or the condition of the surfaces to which they are applied, Van Sickle[®]Paint's liability will under no circumstances exceed replacement of the product.

> Van Sickle Paint PO Box 82222 Lincoln Ne, 68501 1-800-677-2468